

ATOLUX

Baseline 30-S

Baseline 30-S is a suspended luminaire from the Baseline range by Atolux. The luminaire is suspended, directed downward and fitted with a microprismatic optic. The range is intended for offices, museums, healthcare, education, public spaces and leisure venues.

CATEGORY **Pendant luminaires**	MOUNTING **Pendant**	IP CLASS **IP20 (boven) / IP20 (onder)**
COLOUR TEMPERATURE **3000K, 4000K**	CRI **CRI80, CRI90**	UGR **<19**

Introduction

Baseline 30-S is a suspended luminaire from the Baseline range by Atolux. The luminaire is suspended, directed downward and fitted with a microprismatic optic. The range is intended for offices, museums, healthcare, education, public spaces and leisure venues.

With the Baseline 30-S, you choose architectural lighting that unites design and light quality. Designed for kantoren, musea, zorg, education, public spaces, vrijetijdssector, the luminaire integrates neatly into the design and delivers comfortable, considered light. Thanks to its thoughtful detailing and high-quality finish, it is a choice that lasts for years — and makes your project look better.

Technical specifications

Mounting	**Pendant**
Application	**Kantoren, Musea, Zorg, Education, Public spaces, Vrijetijdssector**
Dimensions	**On request**
Material	**(gerecycled) Aluminium (behuizing)**
Optics	**Microprisma**
UGR	**<19**
IP class	**IP20 (boven) / IP20 (onder)**
CRI	**CRI80, CRI90**
CCT	**3000K, 4000K**
Control	**aan/uit, DALI-2, 1-10v, Casambi, On request**
Service life	**L90@50.000 uur**
Voltage / freq.	**220-240V, 50 / 60Hz**
Photobiological safety	**IEC 62471: RG1 (low risk)**
Insulation class	**Class I**
Power factor	**>0.9**
Ambient temperature	**-20°C / +40°C**
Colour	**RAL9016, RAL9005, On request**
Brand	**Atolux**
Category	**Pendant luminaires**

Technical drawings

Dimensions and line art — not to scale



Photometric drawing

Specification text

Baseline 30-S is a suspended luminaire from the Baseline range by Atolux. The luminaire is suspended, directed downward and fitted with a microprismatic optic. The range is intended for offices, museums, healthcare, education, public spaces and leisure venues.

Information

Note

Specifications depend on the project and configuration. Always consult the current technical documentation.

This datasheet is compiled from structured product information held in the Atomis luminaire database. Specifications may vary per project configuration.

Atomis Architectural Lighting · atomislighting.com · The Netherlands

Generated on 31 October 2026