

ATOLUX

# Core-Adjustable 80 White Stucplafond

Core-Adjustable 80 White Stucplafond is a downlight and recessed spotlight from the Core range by Atolux. The luminaire is stuc, directed downward and fitted with a lens. The range is intended for offices, museums, healthcare, education, public spaces, leisure venues and retail.

| CATEGORY | MOUNTING | IP CLASS |
|---|---|---|
| **Downlights & recessed spots** | **Stuc** | **IP54** |

| COLOUR TEMPERATURE | CRI |
|---|---|
| **2700K, 3000K, 4000K,** | **CRI90** |

## Introduction

Core-Adjustable 80 White Stucplafond is a downlight and recessed spotlight from the Core range by Atolux. The luminaire is stuc, directed downward and fitted with a lens. The range is intended for offices, museums, healthcare, education, public spaces, leisure venues and retail.

With the Core-Adjustable 80 White Stucplafond, you choose architectural lighting that unites design and light quality. Designed for kantoren, musea, zorg, education, public spaces, vrijetijdssector, retail, the luminaire integrates neatly into the design and delivers comfortable, considered light. Thanks to its thoughtful detailing and high-quality finish, it is a choice that lasts for years — and makes your project look better.

## Technical specifications

| | |
|---|---|
| Mounting | **Stuc** |
| Application | **Kantoren, Musea, Zorg, Education, Public spaces, Vrijetijdssector, Retail** |
| Material | **Aluminium (behuizing)** |
| Optics | **Lens** |
| IP class | **IP54** |
| CRI | **CRI90** |
| CCT | **2700K, 3000K, 4000K,** |
| Control | **aan/uit, DALI-2** |
| Service life | **L90@100.000 uur** |
| Voltage / freq. | **220-240V, 50 / 60Hz** |
| Efficiency | **100** |
| Photobiological safety | **IEC 62471: RG1 (low risk)** |
| Insulation class | **Class II** |
| Power factor | **>0.9** |
| Ambient temperature | **-20°C / +40°C** |
| Colour | **RAL9016** |
| Brand | **Atolux** |
| Category | **Downlights & recessed spots** |

# Product photos

Atmosphere and product images



## Specification text

Core-Adjustable 80 White Stucplafond is a downlight and recessed spotlight from the Core range by Atolux. The luminaire is stuc, directed downward and fitted with a lens. The range is intended for offices, museums, healthcare, education, public spaces, leisure venues and retail.

# Information

Note

Specifications depend on the project and configuration. Always consult the current technical documentation.

This datasheet is compiled from structured product information held in the Atomis luminaire database. Specifications may vary per project configuration.

---

Atomis Architectural Lighting · atomislighting.com · The Netherlands

Generated on 31 October 2026