

ATOLUX

Cylus-B1 300 Black

Cylus-B1 300 Black is a suspended luminaire from the Cylus range by Atolux. The luminaire is suspended, directed downward and fitted with a reflector. The range is intended for offices, museums, healthcare, education, public spaces and leisure venues.

CATEGORY
Pendant luminaires

MOUNTING
Pendant

IP CLASS
IP20 (boven) / IP20 (onder)

COLOUR TEMPERATURE
3000K, 4000K

CRI
CRI90

Introduction

Cylus-B1 300 Black is a suspended luminaire from the Cylus range by Atolux. The luminaire is suspended, directed downward and fitted with a reflector. The range is intended for offices, museums, healthcare, education, public spaces and leisure venues.

With the Cylus-B1 300 Black, you choose architectural lighting that unites design and light quality. Designed for kantoren, musea, zorg, education, public spaces, vrijetijdssector, the luminaire integrates neatly into the design and delivers comfortable, considered light. Thanks to its thoughtful detailing and high-quality finish, it is a choice that lasts for years — and makes your project look better.

Technical specifications

Mounting	**Pendant**
Application	**Kantoren, Musea, Zorg, Education, Public spaces, Vrijetijdssector**
Dimensions	**300mm**
Material	**Aluminium (behuizing)**
Optics	**Reflector**
IP class	**IP20 (boven) / IP20 (onder)**
CRI	**CRI90**
CCT	**3000K, 4000K**
Control	**aan/uit, DALI-2, 1-10v, Casambi, On request**
Service life	**L90@100.000 uur**
Voltage / freq.	**220-240V, 50 / 60Hz**
Efficiency	**70**
Photobiological safety	**IEC 62471: RG1 (low risk)**
Insulation class	**Class I**
Power factor	**>0.9**
Ambient temperature	**-20°C / +40°C**
Colour	**RAL9005**
Brand	**Atolux**
Category	**Pendant luminaires**

Product photos

Atmosphere and product images



Specification text

Cylus-B1 300 Black is a suspended luminaire from the Cylus range by Atolux. The luminaire is suspended, directed downward and fitted with a reflector. The range is intended for offices, museums, healthcare, education, public spaces and leisure venues.

Information

Note

Specifications depend on the project and configuration. Always consult the current technical documentation.

This datasheet is compiled from structured product information held in the Atomis luminaire database. Specifications may vary per project configuration.

Atomis Architectural Lighting · atomislighting.com · The Netherlands

Generated on 1 November 2026