




ATOLUX

# Eclipse 260 Black

Eclipse 260 Black is a surface-mounted luminaire from the Eclipse range by Atolux. The luminaire is surface-mounted, providing indirect light and fitted with an opal diffuser. The range is intended for offices, healthcare, education, public spaces, leisure venues and retail.

CATEGORY

**Surface-mounted luminaires**

MOUNTING

**Surface-mounted**

IP CLASS

**IP20 (boven) / IP20 (onder)**

COLOUR TEMPERATURE

**3000K**

CRI

**CRI90**

## Introduction

Eclipse 260 Black is a surface-mounted luminaire from the Eclipse range by Atolux. The luminaire is surface-mounted, providing indirect light and fitted with an opal diffuser. The range is intended for offices, healthcare, education, public spaces, leisure venues and retail.

With the Eclipse 260 Black, you choose architectural lighting that unites design and light quality. Designed for kantoren, zorg, education, public spaces, vrijetijdssector, retail, the luminaire integrates neatly into the design and delivers comfortable, considered light. Thanks to its thoughtful detailing and high-quality finish, it is a choice that lasts for years — and makes your project look better.

## Technical specifications

|                        |                                                                   |
|------------------------|-------------------------------------------------------------------|
| Mounting               | Surface-mounted                                                   |
| Application            | Kantoren, Zorg, Education, Public spaces, Vrijtjidssector, Retail |
| Dimensions             | 260mm                                                             |
| Material               | Aluminium (behuizing)                                             |
| Optics                 | Opaal                                                             |
| IP class               | IP20 (boven) / IP20 (onder)                                       |
| CRI                    | CRI90                                                             |
| CCT                    | 3000K                                                             |
| Control                | aan/uit                                                           |
| Voltage / freq.        | 220-240V, 50 / 60Hz                                               |
| Efficiency             | 60                                                                |
| Photobiological safety | IEC 62471: RG1 (low risk)                                         |
| Insulation class       | Class I                                                           |
| Power factor           | >0.9                                                              |
| Ambient temperature    | -20°C / +40°C                                                     |
| Colour                 | RAL9005                                                           |
| Brand                  | Atolux                                                            |
| Category               | Surface-mounted luminaires                                        |

## Product photos

Atmosphere and product images



## Specification text

Eclipse 260 Black is a surface-mounted luminaire from the Eclipse range by Atolux. The luminaire is surface-mounted, providing indirect light and fitted with an opal diffuser. The range is intended for offices, healthcare, education, public spaces, leisure venues and retail.

## Information

### Note

Specifications depend on the project and configuration. Always consult the current technical documentation.

This datasheet is compiled from structured product information held in the Atomis luminaire database. Specifications may vary per project configuration.

Atomis Architectural Lighting · atomislighting.com · The Netherlands

Generated on 31 August 2026