



ATOMIS

Ferro linear 1500

The Ferro linear 1500 is a premium surface-mounted LED luminaire designed for projects where functionality, reliability and a clean, minimalist design come to...

CATEGORY

IP/IK class luminaires

MOUNTING

Surface-mounted

IP CLASS

IP66

COLOUR TEMPERATURE

**2700K, 3000K, 3500K, 4000K, Tun-
able White**

CRI

CRI80, CRI90

UGR

n-v-t-

Introduction

The Ferro linear 1500 is a premium surface-mounted LED luminaire designed for projects where functionality, reliability and a clean, minimalist design come to...

With the Ferro linear 1500, you choose architectural lighting that unites design and light quality. Designed for hospitality, office, education, public spaces, retail, the luminaire integrates neatly into the design and delivers comfortable, considered light. Thanks to its thoughtful detailing and high-quality finish, it is a choice that lasts for years — and makes your project look better.

Features

DALI dimming

Motion sensors

Wireless control options This makes the Ferro linear 1500 suitable for energy-efficient and smart-building solutions

IP40 (for dry indoor spaces)

Diffuser impact resistance: IK05 for PMMA

Dimensions: 1500 mm

Technical specifications

Mounting	Surface-mounted
Application	Hospitality, Office, Education, Public spaces, Retail
Material	Acrylic, Aluminium
Optics	Opal diffuser, Reflector
UGR	n-v-t-
IP class	IP66
CRI	CRI80, CRI90
CCT	2700K, 3000K, 3500K, 4000K, Tunable White
Control	1-10V dimmable, Casambi dimmable, DALI dimmable, Optional
Emergency lighting	1-hour emergency power, Optional, Optional 1-hour autonomy self-test
Efficiency	165lm-w
Photobiological safety	IEC 62471: RG1 (low risk)
Insulation class	Class I, Class II
Power factor	>0.9
Ambient temperature	-20°C / +40°C
Options	220-240V, 50 / 60Hz, 93 100 100 100 100, Integrated, Grey, Cable, L90B50@60, 000h (Tq 25°C), N/A, Downward, On request, On the driver, Rectangular, SDCM=3, White
Brand	Atomis
Category	IP/IK class luminaires

Product photos

Atmosphere and product images



Specification text

The Ferro lineair 1500 is a premium surface-mounted LED luminaire designed for projects where functionality, reliability and a clean, minimalist design come together. Thanks to its round shape and high-quality PMMA optics, this luminaire blends seamlessly into modern interiors in offices, commercial spaces, public buildings and utility projects. - DALI dimming - Motion sensors - Wireless control options This makes the Ferro lineair 1500 suitable for energy-efficient and smart-building solutions - IP40 (for dry indoor spaces) - Diffuser impact resistance: IK05 for PMMA - Dimensions: 1500 mm

Information

Note

Specifications depend on the project and configuration. Always consult the current technical documentation.

This datasheet is compiled from structured product information based on XML source data and the current source page. Specifications may vary per project configuration.

Atomis Architectural Lighting · atomislighting.com · The Netherlands

Generated on 5 July 2026