



ATOLUX

Ferro Round 360

The Ferro Round 360 is a modern, premium surface-mounted LED luminaire designed for projects where functionality, reliability and a clean, minimalist design co...

CATEGORY

IP/IK klasse armaturen

MOUNTING

Surface-mounted

IP CLASS

IP40

COLOUR TEMPERATURE

3000K, 4000K

CRI

CRI80, CRI90

Introduction

The Ferro Round 360 is a modern, premium surface-mounted LED luminaire designed for projects where functionality, reliability and a clean, minimalist design co...

With the Ferro Round 360, you choose architectural lighting that unites design and light quality. Designed for kantoren, zorg, education, public spaces, the luminaire integrates neatly into the design and delivers comfortable, considered light. Thanks to its thoughtful detailing and high-quality finish, it is a choice that lasts for years — and makes your project look better.

Features

DALI dimming

Motion sensors

Wireless control options This makes the Ferro Round 360 suitable for energy-efficient and smart-building solutions

IP40 (for dry indoor spaces)

Diffuser impact resistance: IK05 for PMMA

Dimensions: Ø 360 mm, height 70 mm

Technical specifications

Mounting	Surface-mounted
Application	Kantoren, Zorg, Education, Public spaces
Dimensions	70x360mm
Material	Kunststof (behuizing)
Optics	Opaal
IP class	IP40
CRI	CRI80, CRI90
CCT	3000K, 4000K
Control	aan/uit, DALI-2, 1-10v, Casambi, On request
Emergency lighting	1 uur noodtroom, 1 uur autonomie autotest
Voltage / freq.	220-240V, 50 / 60Hz
Photobiological safety	IEC 62471: RG1 (low risk)
Insulation class	Class II
Power factor	>0.9
Ambient temperature	-20°C / +40°C
Colour	White
Brand	Atolux
Category	IP/IK klasse armaturen

Product photos

Atmosphere and product images



Specification text

The Ferro Round 360 is a modern, premium surface-mounted LED luminaire designed for projects where functionality, reliability and a clean, minimalist design come together. Thanks to its round shape and high-quality PMMA optics, this luminaire blends seamlessly into modern interiors in offices, commercial spaces, public buildings and utility projects. - DALI dimming - Motion sensors - Wireless control options This makes the Ferro Round 360 suitable for energy-efficient and smart-building solutions - IP40 (for dry indoor spaces) - Diffuser impact resistance: IK05 for PMMA - Dimensions: Ø 360 mm, height 70 mm

Information

Note

Specifications depend on the project and configuration. Always consult the current technical documentation.

This datasheet is compiled from structured product information based on XML source data and the current source page. Specifications may vary per project configuration.

Atomis Architectural Lighting · atomislighting.com · The Netherlands

Generated on 25 August 2026