

ATOLUX

Ferro Round 360

The Ferro Round 360 is a modern, premium surface-mounted LED luminaire designed for projects where functionality, reliability and a clean, minimalist design co…

CATEGORY **IP/IK klasse armaturen**	MOUNTING **Surface-mounted**	IP CLASS **IP40**
COLOUR TEMPERATURE **3000K, 4000K**	CRI **CRI80, CRI90**	

Introduction

The Ferro Round 360 is a modern, premium surface-mounted LED luminaire designed for projects where functionality, reliability and a clean, minimalist design co…

With the Ferro Round 360, you choose architectural lighting that unites design and light quality. Designed for kantoren, zorg, education, public spaces, the luminaire integrates neatly into the design and delivers comfortable, considered light. Thanks to its thoughtful detailing and high-quality finish, it is a choice that lasts for years — and makes your project look better.

Features

- DALI dimming
- Motion sensors
- Wireless control options This makes the Ferro Round 360 suitable for energy-efficient and smart-building solutions
- IP40 (for dry indoor spaces)
- Diffuser impact resistance: IK05 for PMMA
- Dimensions: Ø 360 mm, height 70 mm

Technical specifications

Mounting	**Surface-mounted**
Application	**Kantoren, Zorg, Education, Public spaces**
Dimensions	**70x360mm**
Material	**Kunststof (behuizing)**
Optics	**Opaal**
IP class	**IP40**
CRI	**CRI80, CRI90**
CCT	**3000K, 4000K**
Control	**aan/uit, DALI-2, 1-10v, Casambi, On request**
Emergency lighting	**1-hour emergency power, 1 uur autonomie autotest**
Service life	**L90@100.000 uur**
Voltage / freq.	**220-240V, 50 / 60Hz**
Photobiological safety	**IEC 62471: RG1 (low risk)**
Insulation class	**Class II**
Power factor	**>0.9**
Ambient temperature	**-20°C / +40°C**
Colour	**White**
Brand	**Atolux**
Category	**IP/IK klasse armaturen**

Product photos

Atmosphere and product images



Specification text

The Ferro Round 360 is a modern, premium surface-mounted LED luminaire designed for projects where functionality, reliability and a clean, minimalist design come together. Thanks to its round shape and high-quality PMMA optics, this luminaire blends seamlessly into modern interiors in offices, commercial spaces, public buildings and utility projects. - DALI dimming - Motion sensors - Wireless control options This makes the Ferro Round 360 suitable for energy-efficient and smart-building solutions - IP40 (for dry indoor spaces) - Diffuser impact resistance: IK05 for PMMA - Dimensions: Ø 360 mm, height 70 mm

Information

Note

Specifications depend on the project and configuration. Always consult the current technical documentation.

This datasheet is compiled from structured product information based on XML source data and the current source page. Specifications may vary per project configuration.

Atomis Architectural Lighting · atomislighting.com · The Netherlands

Generated on 13 November 2026