



ATOLUX

# Flow 600 Pendel Up/Down

Flow 600 Pendel Up/Down is a suspended luminaire from the Flow range by Atolux. The luminaire is suspended, Omlaag/Omhoog and fitted with a microprismatic optic. The range is intended for offices, healthcare, education, public spaces and leisure venues.

## CATEGORY

**Pendant luminaires**

## MOUNTING

**Pendant**

## IP CLASS

**IP20 (boven) / IP20 (onder)**

## COLOUR TEMPERATURE

**3000K, 3500K, 4000K**

## CRI

**CRI90**

## UGR

**<19**

## Introduction

Flow 600 Pendel Up/Down is a suspended luminaire from the Flow range by Atolux. The luminaire is suspended, Omlaag/Omhoog and fitted with a microprismatic optic. The range is intended for offices, healthcare, education, public spaces and leisure venues.

With the Flow 600 Pendel Up/Down, you choose architectural lighting that unites design and light quality. Designed for kantoren, zorg, education, public spaces, vrijetijdssector, the luminaire integrates neatly into the design and delivers comfortable, considered light. Thanks to its thoughtful detailing and high-quality finish, it is a choice that lasts for years — and makes your project look better.

## Technical specifications

|                        |                                                                  |
|------------------------|------------------------------------------------------------------|
| Mounting               | <b>Pendant</b>                                                   |
| Application            | <b>Kantoren, Zorg, Education, Public spaces, Vrijtjidssector</b> |
| Dimensions             | <b>600mm</b>                                                     |
| Material               | <b>Aluminium (behuizing)</b>                                     |
| Optics                 | <b>Microprisma</b>                                               |
| UGR                    | <b>&lt;19</b>                                                    |
| IP class               | <b>IP20 (boven) / IP20 (onder)</b>                               |
| CRI                    | <b>CRI90</b>                                                     |
| CCT                    | <b>3000K, 3500K, 4000K</b>                                       |
| Control                | <b>aan/uit, DALI-2</b>                                           |
| Voltage / freq.        | <b>220-240V, 50 / 60Hz</b>                                       |
| Efficiency             | <b>100</b>                                                       |
| Photobiological safety | <b>IEC 62471: RG1 (low risk)</b>                                 |
| Insulation class       | <b>Class II</b>                                                  |
| Power factor           | <b>&gt;0.9</b>                                                   |
| Ambient temperature    | <b>-20°C / +40°C</b>                                             |
| Colour                 | <b>RAL9005</b>                                                   |
| Brand                  | <b>Atolux</b>                                                    |
| Category               | <b>Pendant luminaires</b>                                        |

## Product photos

Atmosphere and product images



## Specification text

Flow 600 Pendel Up/Down is a suspended luminaire from the Flow range by Atolux. The luminaire is suspended, Omhoog/Omhoog and fitted with a microprismatic optic. The range is intended for offices, healthcare, education, public spaces and leisure venues.

## Information

### Note

Specifications depend on the project and configuration. Always consult the current technical documentation.

This datasheet is compiled from structured product information held in the Atomis luminaire database. Specifications may vary per project configuration.

Atomis Architectural Lighting · atomislighting.com · The Netherlands

Generated on 31 August 2026