

ATOLUX

Focus-Pin 75 White

Focus-Pin 75 White is a downlight and recessed spotlight from the Focus range by Atolux. The luminaire is recessed, fully adjustable and fitted with a lens. The range is intended for offices, museums, healthcare, education, public spaces, leisure venues and retail.

CATEGORY **Downlights & recessed spots**	MOUNTING **Recessed**	IP CLASS **IP20 (boven) / IP20 (onder)**
COLOUR TEMPERATURE **3000K, 4000K**	CRI **CRI90**	UGR **<6**

Introduction

Focus-Pin 75 White is a downlight and recessed spotlight from the Focus range by Atolux. The luminaire is recessed, fully adjustable and fitted with a lens. The range is intended for offices, museums, healthcare, education, public spaces, leisure venues and retail.

With the Focus-Pin 75 White, you choose architectural lighting that unites design and light quality. Designed for kantoren, musea, zorg, education, public spaces, vrijetijdssector, retail, the luminaire integrates neatly into the design and delivers comfortable, considered light. Thanks to its thoughtful detailing and high-quality finish, it is a choice that lasts for years — and makes your project look better.

Technical specifications

Mounting	**Recessed**
Application	**Kantoren, Musea, Zorg, Education, Public spaces, Vrijetijdssector, Retail**
Dimensions	**75mm**
Material	**Aluminium (behuizing)**
Optics	**Lens**
UGR	**<6**
IP class	**IP20 (boven) / IP20 (onder)**
CRI	**CRI90**
CCT	**3000K, 4000K**
Control	**aan/uit, DALI-2**
Service life	**L90@100.000 uur**
Voltage / freq.	**220-240V, 50 / 60Hz**
Efficiency	**80**
Photobiological safety	**IEC 62471: RG1 (low risk)**
Insulation class	**Class I**
Power factor	**>0.9**
Ambient temperature	**-20°C / +40°C**
Colour	**RAL9016**
Brand	**Atolux**
Category	**Downlights & recessed spots**

Technical drawings

Dimensions and line art — not to scale



Photometric drawing

Specification text

Focus-Pin 75 White is a downlight and recessed spotlight from the Focus range by Atolux. The luminaire is recessed, fully adjustable and fitted with a lens. The range is intended for offices, museums, healthcare, education, public spaces, leisure venues and retail.

Information

Note

Specifications depend on the project and configuration. Always consult the current technical documentation.

This datasheet is compiled from structured product information held in the Atomis luminaire database. Specifications may vary per project configuration.

Atomis Architectural Lighting · atomislighting.com · The Netherlands

Generated on 1 November 2026