



ATOMIS

Fusion Easy-KlimaPlus

Fusion Easy-KlimaPlus is a linear luminaire for use in Interalu Easy-KlimaPlus climate ceilings, with a prismatic lens or an opal diffuser. This LED luminaire ...

CATEGORY

Climate ceiling luminaires

MOUNTING

Recessed

IP CLASS

IP20 (naar boven)/IP40 (naar beneden)

COLOUR TEMPERATURE

2700K, 3000K, 3500K, 4000K, Tunable White

CRI

CR180, CR190

UGR

<19

Introduction

Fusion Easy-KlimaPlus is a linear luminaire for use in Interalu Easy-KlimaPlus climate ceilings, with a prismatic lens or an opal diffuser. This LED luminaire ...

With the Fusion Easy-KlimaPlus, you choose architectural lighting that unites design and light quality. Designed for hospitality, office, education, public spaces, the luminaire integrates neatly into the design and delivers comfortable, considered light. Thanks to its thoughtful detailing and high-quality finish, it is a choice that lasts for years — and makes your project look better.

Features

Integrates seamlessly into Interalu Easy-KlimaPlus metal ceilings

Architectural appearance

Fitted with a prismatic lens (UGR < 19) or an opal diffuser

Technical specifications

| | |
|------------------------|--|
| Mounting | Recessed |
| Application | Hospitality, Office, Education, Public spaces |
| Material | Acrylic, Aluminium, Steel |
| Optics | Microprismatic lens, Opal diffuser |
| UGR | <19 |
| IP class | IP20 (naar boven)/IP40 (naar beneden) |
| CRI | CRI80, CRI90 |
| CCT | 2700K, 3000K, 3500K, 4000K, Tunable White |
| Control | 1-10V dimmable, Casambi dimmable, DALI dimmable, Optional |
| Emergency lighting | 1-hour emergency power, Optional, Optional 1-hour autonomy self-test |
| Efficiency | >140lm/W |
| Photobiological safety | IEC 62471: RG1 (low risk) |
| Insulation class | Class II |
| Power factor | >0.9 |
| Ambient temperature | -20°C / +40°C |
| Options | Attached to the luminaire, Remote driver, Optional, BST 14i2, Europlug, GST18i3, GST18i5 pastelblauw, On request, On the driver |
| Brand | Atomis |
| Category | Climate ceiling luminaires |

Product photos

Atmosphere and product images



Specification text

Fusion Easy-KlimaPlus is a linear luminaire for use in Interalu Easy-KlimaPlus climate ceilings, with a prismatic lens or an opal diffuser. This LED luminaire was developed as an alternative to T5 linear fluorescent luminaires for use in both renovation and new-build projects. - Integrates seamlessly into Interalu Easy-KlimaPlus metal ceilings - Architectural appearance - Fitted with a prismatic lens (UGR < 19) or an opal diffuser

Information

Note

Specifications depend on the project and configuration. Always consult the current technical documentation.

This datasheet is compiled from structured product information based on XML source data and the current source page. Specifications may vary per project configuration.

Atomis Architectural Lighting · atomislighting.com · The Netherlands

Generated on 10 July 2026