

ATOMIS

Fusion-M Linear

Fusion-M Linear is a range of LED luminaires with modular dimensions for use in suspended ceilings. These modules were developed as an alternative to T8 and T5...

CATEGORY

Recessed & lay-in luminaires

MOUNTING

Recessed

IP CLASS

IP20 (naar boven)/IP40 (naar beneden)

COLOUR TEMPERATURE

2700K, 3000K, 3500K, 4000K, Tunable White

CRI

CRI80, CRI90

UGR

<19

Introduction

Fusion-M Linear is a range of LED luminaires with modular dimensions for use in suspended ceilings. These modules were developed as an alternative to T8 and T5...

With the Fusion-M Linear, you choose architectural lighting that unites design and light quality. Designed for hospitality, office, education, public spaces, the luminaire integrates neatly into the design and delivers comfortable, considered light. Thanks to its thoughtful detailing and high-quality finish, it is a choice that lasts for years — and makes your project look better.

Features

Suitable for use with all common grid ceilings

Architectural appearance


Fitted with a prismatic lens (UGR < 19) or an opal diffuser

Technical specifications

Mounting	Recessed
Application	Hospitality, Office, Education, Public spaces
Material	Acrylic, DiBond, Steel
Optics	Microprismatic lens, Opal diffuser
UGR	<19
IP class	IP20 (naar boven)/IP40 (naar beneden)
CRI	CRI80, CRI90
CCT	2700K, 3000K, 3500K, 4000K, Tunable White
Control	1-10V dimmable, Casambi dimmable, DALI dimmable, Optional
Emergency lighting	1-hour emergency power, Optional, Optional 1-hour autonomy self-test
Efficiency	>140lm/W
Photobiological safety	IEC 62471: RG1 (low risk)
Insulation class	Class II
Power factor	>0.9
Ambient temperature	-20°C / +40°C
Options	Remote driver, Optional, BST 14i2, Europlug, GST18i3, GST18i5 pastel-blauw, On request, On the driver
Brand	Atomis
Category	Recessed & lay-in luminaires


Product photos

Atmosphere and product images — technical drawings are on a separate page



Technical drawings

Dimensions and line art — not to scale



Photometric drawing

Specification text

Fusion-M Linear is a range of LED luminaires with modular dimensions for use in suspended ceilings. These modules were developed as an alternative to T8 and T5 fluorescent luminaires for use in both renovation and new-build projects. - Suitable for use with all common grid ceilings - Architectural appearance - Fitted with a prismatic lens (UGR < 19) or an opal diffuser

Information

Note

Specifications depend on the project and configuration. Always consult the current technical documentation.

This datasheet is compiled from structured product information based on XML source data and the current source page. Specifications may vary per project configuration.

Atomis Architectural Lighting · atomislighting.com · The Netherlands

Generated on 9 July 2026