



ATOMIS

Interline-SAPP

Seamless line lighting for Interalu SAPP — sleek, flexible and comfortable (low UGR).
Atolux Interline SAPP is a minimalist, elegant linear luminaire that blen...

CATEGORY

Climate ceiling luminaires, Baffle luminaires

MOUNTING

Recessed

IP CLASS

IP20 (naar boven)/IP40 (naar beneden)

COLOUR TEMPERATURE

2700K, 3000K, 4000K

CRI

CRI90

UGR

<19

Introduction

Seamless line lighting for Interalu SAPP — sleek, flexible and comfortable (low UGR). Atolux Interline SAPP is a minimalist, elegant linear luminaire that blen...

With the Interline-SAPP, you choose architectural lighting that unites design and light quality. Designed for hospitality, office, education, public spaces, the luminaire integrates neatly into the design and delivers comfortable, considered light. Thanks to its thoughtful detailing and high-quality finish, it is a choice that lasts for years — and makes your project look better.

Features

sleek, flexible and comfortable (low UGR). Atolux Interline SAPP is a minimalist, elegant linear luminaire that blends seamlessly into the Interalu SAPP baffle ceiling. Thanks to its smart spring-clip mechanism, you simply click the luminaire into the joint—quick to install and effortless to reposition later when the layout of the space changes. The combination of clean design and high-quality optics delivers a pleasant, calm light effect. The matt black optics provide pleasant visual comfort with a low UGR, ideal for screen-based workstations and modern office environments. With an efficiency of >130 lm/W and a high CRI of 90, Interline SAPP combines maximum light output with natural colour rendering—perfect for high-quality task lighting compliant with EN 12464-1 for office applications. It is practical too: the luminaire comes standard with a DALI-2 driver, including a 5-metre link cable between driver and luminaire and a GST18i5 male/female compatible connection on the driver for fast, error-free installation and through-wiring. Available in a white or black coating, so the luminaire always matches the ceiling and interior concept. Dimensions: W21×L850, W21×L1130, W21×L1410

Technical specifications

Mounting	Recessed
Application	Hospitality, Office, Education, Public spaces
Material	Acrylic, Steel
Optics	Lens and louvre
UGR	<19
IP class	IP20 (naar boven)/IP40 (naar beneden)
CRI	CRI90
CCT	2700K, 3000K, 4000K
Control	1-10V dimmable, Casambi dimmable, DALI dimmable, Optional
Emergency lighting	1-hour emergency power, Optional, Optional 1-hour autonomy self-test
Efficiency	>130lm/W
Photobiological safety	IEC 62471: RG1 (low risk)
Insulation class	Class II
Power factor	>0.9
Ambient temperature	-20°C / +40°C
Options	220-240V, 50 / 60Hz, 93 100 100 100 100, BST 14i2, Europlug, GST18i3, GST18i5 pastelblauw, L90B50@60, 000h (Tq 25°C), Remote driver, N/A, Downward, On request, On the driver, Rectangular, SDCM=3
Brand	Atomis
Category	Climate ceiling luminaires, Baffle luminaires

Product photos

Atmosphere and product images



Specification text

Seamless line lighting for Interlu SAPP — sleek, flexible and comfortable (low UGR). Atolux Interline SAPP is a minimalist, elegant linear luminaire that blends seamlessly into the Interlu SAPP baffle ceiling. Thanks to its smart spring-clip mechanism, you simply click the luminaire into the joint—quick to install and effortless to reposition later when the layout of the space changes. The combination of clean design and high-quality optics delivers a pleasant, calm light effect. The matt black optics provide pleasant visual comfort with a low UGR, ideal for screen-based workstations and modern office environments. With an efficiency of >130 lm/W and a high CRI of 90, Interline SAPP combines maximum light output with natural colour rendering—perfect for high-quality task lighting compliant with EN 12464-1 for office applications. It is practical too: the luminaire comes standard with a DALI-2 driver, including a 5-metre link cable between driver and luminaire and a GST18i5 male/female compatible connection on the driver for fast, error-free installation and through-wiring. Available in a white or black coating, so the luminaire always matches the ceiling and interior concept. Dimensions: W21×L850, W21×L1130, W21×L1410

Information

Note

Specifications depend on the project and configuration. Always consult the current technical documentation.

This datasheet is compiled from structured product information based on XML source data and the current source page. Specifications may vary per project configuration.

Atomis Architectural Lighting · atomislighting.com · The Netherlands

Generated on 5 July 2026