

ATOLUX

Interline-SAPP Opaal 610

Interline-SAPP Opaal 610 is a climate ceiling and baffle luminaire from the Interline range by Atolux. The luminaire is lay-in, directed downward and fitted with an opal diffuser. The range is intended for offices, healthcare, education, public spaces and leisure venues.

CATEGORY	MOUNTING	IP CLASS
Climate ceiling luminaires, Baffle luminaires	**Inleg**	**IP20 (boven) / IP20 (onder)**

COLOUR TEMPERATURE	CRI	UGR
3000K, 4000K	**CRI90**	**<22**

Introduction

Interline-SAPP Opaal 610 is a climate ceiling and baffle luminaire from the Interline range by Atolux. The luminaire is lay-in, directed downward and fitted with an opal diffuser. The range is intended for offices, healthcare, education, public spaces and leisure venues.

With the Interline-SAPP Opaal 610, you choose architectural lighting that unites design and light quality. Designed for kantoren, zorg, education, public spaces, vrijetijdssector, the luminaire integrates neatly into the design and delivers comfortable, considered light. Thanks to its thoughtful detailing and high-quality finish, it is a choice that lasts for years — and makes your project look better.

Technical specifications

Mounting	**Inleg**
Application	**Kantoren, Zorg, Education, Public spaces, Vrijetijdssector**
Dimensions	**21x610mm**
Material	**Aluminium (behuizing)**
Optics	**Opaal**
UGR	**<22**
IP class	**IP20 (boven) / IP20 (onder)**
CRI	**CRI90**
CCT	**3000K, 4000K**
Control	**aan/uit, DALI-2, 1-10v, Casambi, On request**
Emergency lighting	**1-hour emergency power, 1 uur autonomie autotest**
Service life	**L90@50.000 uur**
Voltage / freq.	**220-240V, 50 / 60Hz**
Efficiency	**115**
Photobiological safety	**IEC 62471: RG1 (low risk)**
Insulation class	**Class II**
Power factor	**>0.9**
Ambient temperature	**-20°C / +40°C**
Colour	**RAL9016, RAL9005, On request**
Brand	**Atolux**
Category	**Climate ceiling luminaires, Baffle luminaires**

Product photos

Atmosphere and product images



Specification text

Interline-SAPP Opaal 610 is a climate ceiling and baffle luminaire from the Interline range by Atolux. The luminaire is lay-in, directed downward and fitted with an opal diffuser. The range is intended for offices, healthcare, education, public spaces and leisure venues.

Information

Note

Specifications depend on the project and configuration. Always consult the current technical documentation.

This datasheet is compiled from structured product information held in the Atomis luminaire database. Specifications may vary per project configuration.

Atomis Architectural Lighting · atomislighting.com · The Netherlands

Generated on 6 November 2026