


ATOLUX

# Interline-WEC Opaal 1510

Interline-WEC Opaal 1510 is a climate ceiling and baffle luminaire from the Interline range by Atolux. The luminaire is lay-in, directed downward and fitted with an opal diffuser. The range is intended for offices, healthcare, education, public spaces and leisure venues.

| CATEGORY | MOUNTING | IP CLASS |
|---|---|---|
| **Climate ceiling luminaires, Baffle luminaires** | **Inleg** | **IP20 (boven) / IP20 (onder)** |
| **COLOUR TEMPERATURE** | **CRI** | **UGR** |
| **3000K, 4000K** | **CRI90** | **<22** |

## Introduction

Interline-WEC Opaal 1510 is a climate ceiling and baffle luminaire from the Interline range by Atolux. The luminaire is lay-in, directed downward and fitted with an opal diffuser. The range is intended for offices, healthcare, education, public spaces and leisure venues.


With the Interline-WEC Opaal 1510, you choose architectural lighting that unites design and light quality. Designed for kantoren, zorg, education, public spaces, vrijetijdssector, the luminaire integrates neatly into the design and delivers comfortable, considered light. Thanks to its thoughtful detailing and high-quality finish, it is a choice that lasts for years — and makes your project look better.

# Technical specifications

| | |
|---|---|
| Mounting | **Inleg** |
| Application | **Kantoren, Zorg, Education, Public spaces, Vrijetijdssector** |
| Dimensions | **21x1510mm** |
| Material | **Aluminium (behuizing)** |
| Optics | **Opaal** |
| UGR | **<22** |
| IP class | **IP20 (boven) / IP20 (onder)** |
| CRI | **CRI90** |
| CCT | **3000K, 4000K** |
| Control | **aan/uit, DALI-2, 1-10v, Casambi, On request** |
| Emergency lighting | **1-hour emergency power, 1 uur autonomie autotest** |
| Service life | **L90@50.000 uur** |
| Voltage / freq. | **220-240V, 50 / 60Hz** |
| Efficiency | **115** |
| Photobiological safety | **IEC 62471: RG1 (low risk)** |
| Insulation class | **Class II** |
| Power factor | **>0.9** |
| Ambient temperature | **-20°C / +40°C** |
| Colour | **RAL9016, RAL9005, On request** |
| Brand | **Atolux** |
| Category | **Climate ceiling luminaires, Baffle luminaires** |

# Product photos

Atmosphere and product images



## Specification text

Interline-WEC Opaal 1510 is a climate ceiling and baffle luminaire from the Interline range by Atolux. The luminaire is lay-in, directed downward and fitted with an opal diffuser. The range is intended for offices, healthcare, education, public spaces and leisure venues.

# Information

Note

Specifications depend on the project and configuration. Always consult the current technical documentation.

This datasheet is compiled from structured product information held in the Atomis luminaire database. Specifications may vary per project configuration.

Atomis Architectural Lighting · atomislighting.com · The Netherlands

Generated on 27 November 2026