



ATOMIS

Lightscape-C 80

Lightscape-C 80 is a linear pendant luminaire fitted with a microprismatic lens (low UGR).

CATEGORY

Surface-mounted luminaires

MOUNTING

Ceiling-mounted

IP CLASS

IP20 (naar boven)/IP40 (naar beneden)

COLOUR TEMPERATURE

2700K, 3000K, 3500K, 4000K, Tunable White

CRI

CR180, CR190

UGR

<19

Introduction

Lightscape-C 80 is a linear pendant luminaire fitted with a microprismatic lens (low UGR).

With the Lightscape-C 80, you choose architectural lighting that unites design and light quality. Designed for hospitality, office, education, public spaces, the luminaire integrates neatly into the design and delivers comfortable, considered light. Thanks to its thoughtful detailing and high-quality finish, it is a choice that lasts for years — and makes your project look better.

Features

Architectural design that provides uniform lighting along the entire length of the luminaire

Office lighting

Prismatic lens, low UGR

Technical specifications

Mounting	Ceiling-mounted
Application	Hospitality, Office, Education, Public spaces
Material	Acrylic, Aluminium
Optics	Microprismatic lens, Opal diffuser
UGR	<19
IP class	IP20 (naar boven)/IP40 (naar beneden)
CRI	CRI80, CRI90
CCT	2700K, 3000K, 3500K, 4000K, Tunable White
Control	1-10V dimmable, Casambi dimmable, DALI dimmable, Optional
Emergency lighting	1-hour emergency power, Optional, Optional 1-hour autonomy self-test
Efficiency	>140lm/W
Photobiological safety	IEC 62471: RG1 (low risk)
Insulation class	Class II
Power factor	>0.9
Ambient temperature	-20°C / +40°C
Options	220-240V, 50 / 60Hz, 93 100 100 100 100, BST 14i2, Europlug, Integrated, GST18i3, GST18i5 pastelblauw, L90B50@60, 000h (Tq 25°C), N/A, Downward, On request, On the driver, Rectangular, SDCM=3
Brand	Atomis
Category	Surface-mounted luminaires

Product photos

Atmosphere and product images — technical drawings are on a separate page



Technical drawings

Dimensions and line art — not to scale



Photometric drawing

Specification text

Lightscape-C 80 is a linear pendant luminaire fitted with a microprismatic lens (low UGR). - Architectural design that provides uniform lighting along the entire length of the luminaire - Office lighting - Prismatic lens, low UGR

Information

Note

Specifications depend on the project and configuration. Always consult the current technical documentation.

This datasheet is compiled from structured product information based on XML source data and the current source page. Specifications may vary per project configuration.

Atomis Architectural Lighting · atomislighting.com · The Netherlands

Generated on 9 July 2026