

ATOMIS

Lightscape-C 80

Lightscape-C 80 is a linear pendant luminaire fitted with a microprismatic lens (low UGR).

CATEGORY **Surface-mounted luminaires**	MOUNTING **Surface-mounted**	IP CLASS **IP20 (boven) / IP20 (onder)**
COLOUR TEMPERATURE **2700K, 3000K, 4000K, Tunable white, op aanvraag**	CRI **CRI80, CRI90**	UGR **<19**

Introduction

Lightscape-C 80 is a linear pendant luminaire fitted with a microprismatic lens (low UGR).

With the Lightscape 80-C, you choose architectural lighting that unites design and light quality. Designed for kantoren, zorg, education, public spaces, vrijetijdssector, the luminaire integrates neatly into the design and delivers comfortable, considered light. Thanks to its thoughtful detailing and high-quality finish, it is a choice that lasts for years — and makes your project look better.

Technical specifications

Mounting	**Surface-mounted**
Application	**Kantoren, Zorg, Education, Public spaces, Vrijetijdssector**
Dimensions	**On request**
Material	**Aluminium (behuizing)**
Optics	**Microprisma**
UGR	**<19**
IP class	**IP20 (boven) / IP20 (onder)**
CRI	**CRI80, CRI90**
CCT	**2700K, 3000K, 4000K, Tunable white, On request**
Control	**aan/uit, DALI-2, 1-10v, Casambi, On request**
Emergency lighting	**1-hour emergency power, 1 uur autonomie autotest**
Service life	**L90@50.000 uur**
Voltage / freq.	**220-240V, 50 / 60Hz**
Efficiency	**>140lm/W**
Photobiological safety	**IEC 62471: RG1 (low risk)**
Insulation class	**Class I**
Power factor	**>0.9**
Ambient temperature	**-20°C / +40°C**
Colour	**RAL9016, RAL9005, On request**
Options	**220-240V, 50 / 60Hz, 93 100 100 100 100, BST 14i2, Europlug, Integrated, GST18i3, GST18i5 pastelblauw, L90B50@60, 000h (Tq 25°C), N/A, Downward, On request, On the driver, Rectangular, SDCM=3**
Brand	**Atomis**
Category	**Surface-mounted luminaires**

Technical drawings

Dimensions and line art — not to scale



Photometric drawing

Specification text

Lightscape 80-C is a surface-mounted luminaire from the Lightscape range by Atomis. The luminaire is surface-mounted, directed downward and fitted with a microprismatic optic. The range is intended for offices, healthcare, education, public spaces and leisure venues.

Information

Note

Specifications depend on the project and configuration. Always consult the current technical documentation.

This datasheet is compiled from structured product information held in the Atomis luminaire database. Specifications may vary per project configuration.

Atomis Architectural Lighting · atomislighting.com · The Netherlands

Generated on 8 November 2026