



ATOMIS

Linterna-K

Linterna-K is a linear LED luminaire with a parabolic batwing louvre for use in climate ceilings.

CATEGORY

Climate ceiling luminaires

MOUNTING

Inleg

IP CLASS

IP20 (boven) / IP20 (onder)

COLOUR TEMPERATURE

**2700K, 3000K, 4000K, Tunable
white, op aanvraag**

CRI

CRI80, CRI90

UGR

<19

Introduction

Linterna-K is a linear LED luminaire with a parabolic batwing louvre for use in climate ceilings.


With the Linterna-K, you choose architectural lighting that unites design and light quality. Designed for kantoren, zorg, education, public spaces, vrijetijdssector, the luminaire integrates neatly into the design and delivers comfortable, considered light. Thanks to its thoughtful detailing and high-quality finish, it is a choice that lasts for years — and makes your project look better.



Technical specifications

Mounting	Inleg
Application	Kantoren, Zorg, Education, Public spaces, Vrijtjidssector
Dimensions	On request
Material	Staal (behuizing)
Optics	Parabool reflector
UGR	<19
IP class	IP20 (boven) / IP20 (onder)
CRI	CRI80, CRI90
CCT	2700K, 3000K, 4000K, Tunable white, On request
Control	aan/uit, DALI-2, 1-10v, Casambi, On request
Emergency lighting	1 uur noodtroom, 1 uur autonomie autotest
Voltage / freq.	220-240V, 50 / 60Hz
Photobiological safety	IEC 62471: RG1 (low risk)
Insulation class	Class II
Power factor	>0.9
Ambient temperature	-20°C / +40°C
Colour	RAL9016, RAL9005, On request
Brand	Atomis
Category	Climate ceiling luminaires

Product photos

Atmosphere and product images





Specification text

Linterna-K is a linear LED luminaire with a parabolic batwing louvre for use in climate ceilings. Its light distribution supports good uniformity at large luminaire spacings of up to around 3 metres. This makes the luminaire suitable for projects where climate-ceiling integration, visual comfort and a controlled light distribution must come together.

Information

Note

Specifications depend on the project and configuration. Always consult the current technical documentation.

This datasheet is compiled from structured product information based on XML source data and the current source page. Specifications may vary per project configuration.

Atomis Architectural Lighting · atomislighting.com · The Netherlands

Generated on 14 August 2026