



ATOLUX

LumaCore DLS 180 downlight

LumaCore DLS 180 downlight is a downlight and recessed spotlight from the LumaCore range by Atolux. The luminaire is recessed, directed downward and fitted with an opal diffuser. The range is intended for offices, museums, healthcare, education, public spaces, leisure venues and retail.

CATEGORY

Downlights & recessed spots

MOUNTING

Recessed

IP CLASS

IP20 (boven) / IP20 (onder)

COLOUR TEMPERATURE

3000K, 4000K

CRI

CRI80, CRI90

UGR

<19

Introduction

LumaCore DLS 180 downlight is a downlight and recessed spotlight from the LumaCore range by Atolux. The luminaire is recessed, directed downward and fitted with an opal diffuser. The range is intended for offices, museums, healthcare, education, public spaces, leisure venues and retail.

With the LumaCore DLS 180 downlight, you choose architectural lighting that unites design and light quality. Designed for kantoren, musea, zorg, education, public spaces, vrijetijdssector, retail, the luminaire integrates neatly into the design and delivers comfortable, considered light. Thanks to its thoughtful detailing and high-quality finish, it is a choice that lasts for years — and makes your project look better.

Technical specifications

Mounting	Recessed
Application	Kantoren, Musea, Zorg, Education, Public spaces, Vrijetijdssector, Retail
Dimensions	180mm
Material	Aluminium (behuizing)
Optics	Opaal
UGR	<19
IP class	IP20 (boven) / IP20 (onder)
CRI	CRI80, CRI90
CCT	3000K, 4000K
Control	aan/uit, DALI-2, 1-10v, Casambi, On request
Emergency lighting	1 uur noodtroom, 1 uur autonomie autotest
Voltage / freq.	220-240V, 50 / 60Hz
Photobiological safety	IEC 62471: RG1 (low risk)
Insulation class	Class II
Power factor	>0.9
Ambient temperature	-20°C / +40°C
Colour	White
Brand	Atolux
Category	Downlights & recessed spots

Product photos

Atmosphere and product images



Specification text

LumaCore DLS 180 downlight is a downlight and recessed spotlight from the LumaCore range by Atolux. The luminaire is recessed, directed downward and fitted with an opal diffuser. The range is intended for offices, museums, healthcare, education, public spaces, leisure venues and retail.

Information

Note

Specifications depend on the project and configuration. Always consult the current technical documentation.

This datasheet is compiled from structured product information held in the Atomis luminaire database. Specifications may vary per project configuration.

Atomis Architectural Lighting · atomislighting.com · The Netherlands

Generated on 31 August 2026