

ATOMIS

Meson round 190-C

Meson round 190-C is a premium surface-mounted LED downlight with power LEDs covered by a prismatic lens or a double satin diffuser. The cap is recessed into t…

CATEGORY	MOUNTING	IP CLASS
Surface-mounted luminaires	**Recessed**	**IP20 (boven) / IP20 (onder)**
COLOUR TEMPERATURE	**CRI**	**UGR**
2700K, 3000K, 4000K, Tunable white, op aanvraag	**CRI80, CRI90**	**<22**

Introduction

Meson round 190-C is a premium surface-mounted LED downlight with power LEDs covered by a prismatic lens or a double satin diffuser. The cap is recessed into t…

With the Meson round 190-C, you choose architectural lighting that unites design and light quality. Designed for kantoren, zorg, education, public spaces, vrijetijdssector, the luminaire integrates neatly into the design and delivers comfortable, considered light. Thanks to its thoughtful detailing and high-quality finish, it is a choice that lasts for years — and makes your project look better.

Features

- Housing in matt white or matt black
- Reflector ring available in matt anodised, gloss anodised, matt black or matt white
- Opal diffuser or prismatic lens
- Versions with emergency lighting available

Technical specifications

Mounting	**Recessed**
Application	**Kantoren, Zorg, Education, Public spaces, Vrijetijdssector**
Dimensions	**190mm**
Material	**Staal (behuizing)**
Optics	**Opaal**
UGR	**<22**
IP class	**IP20 (boven) / IP20 (onder)**
CRI	**CRI80, CRI90**
CCT	**2700K, 3000K, 4000K, Tunable white, On request**
Control	**aan/uit, DALI-2, 1-10v, Casambi, On request**
Emergency lighting	**1-hour emergency power, 1 uur autonomie autotest**
Service life	**L90@100.000 uur**
Voltage / freq.	**220-240V, 50 / 60Hz**
Photobiological safety	**IEC 62471: RG1 (low risk)**
Insulation class	**Class I**
Power factor	**>0.9**
Ambient temperature	**-20°C / +40°C**
Colour	**RAL9016, RAL9005, On request**
Brand	**Atomis**
Category	**Surface-mounted luminaires**

Product photos

Atmosphere and product images



Specification text

Meson round 190-C is a premium surface-mounted LED downlight with power LEDs covered by a prismatic lens or a double satin diffuser. The cap is recessed into the trim, combined with a matt or high-gloss glare-reducing reflector. - Housing in matt white or matt black - Reflector ring available in matt anodised, gloss anodised, matt black or matt white - Opal diffuser or prismatic lens - Versions with emergency lighting available

Information

Note

Specifications depend on the project and configuration. Always consult the current technical documentation.

This datasheet is compiled from structured product information based on XML source data and the current source page. Specifications may vary per project configuration.

Atomis Architectural Lighting · atomislighting.com · The Netherlands

Generated on 27 November 2026