



ATOMIS

Metronome-B

Metronome-B is a linear LED luminaire fitted with 20, 28 or 36 lenses, recessed behind a louvre grille, for use in grid (bandraaster) ceilings. This LED luminai...

CATEGORY

Recessed & lay-in luminaires

MOUNTING

Inleg

IP CLASS

IP20 (boven) / IP20 (onder)

COLOUR TEMPERATURE

**2700K, 3000K, 4000K, Tunable
white, op aanvraag**

CRI

CRI80, CRI90

UGR

<19

Introduction

Metronome-B is a linear LED luminaire fitted with 20, 28 or 36 lenses, recessed behind a louvre grille, for use in grid (bandraaster) ceilings. This LED luminai...

With the Metronome-B, you choose architectural lighting that unites design and light quality. Designed for kantoren, zorg, education, public spaces, vrijetijdssector, the luminaire integrates neatly into the design and delivers comfortable, considered light. Thanks to its thoughtful detailing and high-quality finish, it is a choice that lasts for years — and makes your project look better.

Features

Architectural appearance with 20, 28 or 36 optics

Choice between UGR < 19 and UGR < 16 optics

Louvre finish in white or high-gloss aluminium

Flat design for low ceiling depths

Technical specifications

Mounting	Inleg
Application	Kantoren, Zorg, Education, Public spaces, Vrijtjidssector
Dimensions	On request
Material	Staal (behuizing)
Optics	Lens met Louver
UGR	<19
IP class	IP20 (boven) / IP20 (onder)
CRI	CRI80, CRI90
CCT	2700K, 3000K, 4000K, Tunable white, On request
Control	aan/uit, DALI-2, 1-10v, Casambi, On request
Emergency lighting	1-hour emergency power, 1 uur autonomie autotest
Voltage / freq.	220-240V, 50 / 60Hz
Photobiological safety	IEC 62471: RG1 (low risk)
Insulation class	Class II
Power factor	>0.9
Ambient temperature	-20°C / +40°C
Colour	RAL9016, RAL9005, On request
Brand	Atomis
Category	Recessed & lay-in luminaires

Product photos

Atmosphere and product images



Specification text

Metronome-B is a linear LED luminaire fitted with 20, 28 or 36 lenses, recessed behind a louvre grille, for use in grid (bandraster) ceilings. This LED luminaire is an entirely new lighting solution for effective lighting with an architectural appearance. A choice can be made between UGR < 19 and UGR < 16 optics. - Architectural appearance with 20, 28 or 36 optics - Choice between UGR < 19 and UGR < 16 optics - Louvre finish in white or high-gloss aluminium - Flat design for low ceiling depths

Information

Note

Specifications depend on the project and configuration. Always consult the current technical documentation.

This datasheet is compiled from structured product information based on XML source data and the current source page. Specifications may vary per project configuration.

Atomis Architectural Lighting · atomislighting.com · The Netherlands

Generated on 10 September 2026