



ATOMIS

Miro-M 600x600 model 2

Miro-M 600x600 Model 2 is a square LED luminaire with 32 recessed lenses placed behind a louvre grille. This innovative luminaire provides effective lighting a...

CATEGORY

Recessed & lay-in luminaires

MOUNTING

Recessed

IP CLASS

IP20 (naar boven)/IP40 (naar beneden)

COLOUR TEMPERATURE

2700K, 3000K, 3500K, 4000K, Tunable White

CRI

CRI80, CRI90, CRI97

UGR

<19

Introduction

Miro-M 600x600 Model 2 is a square LED luminaire with 32 recessed lenses placed behind a louvre grille. This innovative luminaire provides effective lighting a...

With the Miro-M 600x600 model 2, you choose architectural lighting that unites design and light quality. Thanks to its thoughtful detailing and high-quality finish, it is a choice that lasts for years — and makes your project look better.

Features

Architectural design with 32 optics

Choice between UGR < 19 and UGR < 16 optics

Louvre in matt black and matt white

Flat design for low ceiling depths

Technical specifications

Mounting	Recessed
Material	Acrylic, Steel
Optics	Lens and louvre
UGR	<19
IP class	IP20 (naar boven)/IP40 (naar beneden)
CRI	CRI80, CRI90, CRI97
CCT	2700K, 3000K, 3500K, 4000K, Tunable White
Control	1-10V dimmable, Casambi dimmable, DALI dimmable, Optional
Emergency lighting	1-hour emergency power, Optional, Optional 1-hour autonomy self-test
Efficiency	>140lm/W
Photobiological safety	IEC 62471: RG1 (low risk)
Insulation class	Class II
Power factor	>0.9
Ambient temperature	-20°C / +40°C
Options	93 100 100 100 100, Attached to the luminaire, BST 14i2, Europlug, GST18i3, GST18i5 pastelblauw, L90B50@60, 000h (Tq 25°C), Remote driver, Downward, On request, On the driver, Optional, SDCM=3, Square
Brand	Atomis
Category	Recessed & lay-in luminaires

Technical drawings

Dimensions and line art — not to scale



Photometric drawing

Specification text

Miro-M 600×600 Model 2 is a square LED luminaire with 32 recessed lenses placed behind a louvre grille. This innovative luminaire provides effective lighting and adds elegance to any architectural environment. Customers can choose between two different optics: the standard UGR < 19 or the UGR < 16. The luminaires are made of powder-coated steel and are custom-made for each ceiling system. - Architectural design with 32 optics - Choice between UGR < 19 and UGR < 16 optics - Louvre in matt black and matt white - Flat design for low ceiling depths

Information

Note

Specifications depend on the project and configuration. Always consult the current technical documentation.

This datasheet is compiled from structured product information based on XML source data and the current source page. Specifications may vary per project configuration.

Atomis Architectural Lighting · atomislighting.com · The Netherlands

Generated on 7 July 2026