


ATOMIS

Miro-Track

Miro-Track is a track luminaire from the Miro range by Atomis. The luminaire is track, directed downward and fitted with a lens with louvre. The range is intended for offices, healthcare, education, public spaces and leisure venues.

CATEGORY **Track luminaires**	MOUNTING **Track**	IP CLASS **IP20 (boven) / IP20 (onder)**
COLOUR TEMPERATURE **2700K, 3000K, 4000K, Tunable white, op aanvraag**	CRI **CRI80, CRI90**	UGR **<19**

Introduction

Miro-Track is a track luminaire from the Miro range by Atomis. The luminaire is track, directed downward and fitted with a lens with louvre. The range is intended for offices, healthcare, education, public spaces and leisure venues.

With the Miro-Track, you choose architectural lighting that unites design and light quality. Designed for kantoren, zorg, education, public spaces, vrijetijdssector, the luminaire integrates neatly into the design and delivers comfortable, considered light. Thanks to its thoughtful detailing and high-quality finish, it is a choice that lasts for years — and makes your project look better.

Technical specifications

Mounting	**Track**
Application	**Kantoren, Zorg, Education, Public spaces, Vrijetijdssector**
Dimensions	**On request**
Material	**Staal (behuizing)**
Optics	**Lens met Louver**
UGR	**<19**
IP class	**IP20 (boven) / IP20 (onder)**
CRI	**CRI80, CRI90**
CCT	**2700K, 3000K, 4000K, Tunable white, On request**
Control	**aan/uit, DALI-2, 1-10v, Casambi, On request**
Emergency lighting	**1-hour emergency power, 1 uur autonomie autotest**
Service life	**L90@50.000 uur**
Voltage / freq.	**220-240V, 50 / 60Hz**
Photobiological safety	**IEC 62471: RG1 (low risk)**
Insulation class	**Class I**
Power factor	**>0.9**
Ambient temperature	**-20°C / +40°C**
Colour	**RAL9016, RAL9005, On request**
Brand	**Atomis**
Category	**Track luminaires**

Product photos

Atmosphere and product images



Specification text

Miro-Track is a track luminaire from the Miro range by Atomis. The luminaire is track, directed downward and fitted with a lens with louvre. The range is intended for offices, healthcare, education, public spaces and leisure venues.

Information

Note

Specifications depend on the project and configuration. Always consult the current technical documentation.

This datasheet is compiled from structured product information held in the Atomis luminaire database. Specifications may vary per project configuration.

Atomis Architectural Lighting · atomislighting.com · The Netherlands

Generated on 2 November 2026