

ATOMIS

Myos-M 300x1500

Myos-M 300x1500 is a recessed and lay-in luminaire from the Myos range by Atomis. The luminaire is lay-in, directed downward and fitted with a Multioptic lens. The range is intended for offices, healthcare, education, public spaces and leisure venues.

CATEGORY **Recessed & lay-in luminaires**	MOUNTING **Inleg**	IP CLASS **IP20 (boven) / IP20 (onder)**
COLOUR TEMPERATURE **3000K, 4000K**	CRI **CRI80, CRI90**	UGR **<19**

Introduction

Myos-M 300x1500 is a recessed and lay-in luminaire from the Myos range by Atomis. The luminaire is lay-in, directed downward and fitted with a Multioptic lens. The range is intended for offices, healthcare, education, public spaces and leisure venues.

With the Myos-M 300x1500, you choose architectural lighting that unites design and light quality. Designed for kantoren, zorg, education, public spaces, vrijetijdssector, the luminaire integrates neatly into the design and delivers comfortable, considered light. Thanks to its thoughtful detailing and high-quality finish, it is a choice that lasts for years — and makes your project look better.

Technical specifications

Mounting	**Inleg**
Application	**Kantoren, Zorg, Education, Public spaces, Vrijetijdssector**
Dimensions	**295x1495mm**
Material	**Staal (behuizing)**
Optics	**MultiopticLens**
UGR	**<19**
IP class	**IP20 (boven) / IP20 (onder)**
CRI	**CRI80, CRI90**
CCT	**3000K, 4000K**
Control	**aan/uit, DALI-2, 1-10v, Casambi, On request**
Emergency lighting	**1-hour emergency power, 1 uur autonomie autotest**
Service life	**L90@50.000 uur**
Voltage / freq.	**220-240V, 50 / 60Hz**
Photobiological safety	**IEC 62471: RG1 (low risk)**
Insulation class	**Class II**
Power factor	**>0.9**
Ambient temperature	**-20°C / +40°C**
Colour	**RAL9016, RAL9005, On request**
Brand	**Atomis**
Category	**Recessed & lay-in luminaires**

Product photos

Atmosphere and product images



Specification text

Myos-M 300x1500 is a recessed and lay-in luminaire from the Myos range by Atomis. The luminaire is lay-in, directed downward and fitted with a Multioptic lens. The range is intended for offices, healthcare, education, public spaces and leisure venues.

Information

Note

Specifications depend on the project and configuration. Always consult the current technical documentation.

This datasheet is compiled from structured product information held in the Atomis luminaire database. Specifications may vary per project configuration.

Atomis Architectural Lighting · atomislighting.com · The Netherlands

Generated on 2 November 2026