

ATOMIS

Myos-M 600x600

A range of recessed luminaires with mid-power LED modules using Multioptic® lens technology, specially designed for use with exposed grid ceilings. Myos-M 600x…

CATEGORY	MOUNTING	IP CLASS
Recessed & lay-in luminaires	**Inleg**	**IP20 (boven) / IP20 (onder)**
COLOUR TEMPERATURE	**CRI**	**UGR**
3000K, 4000K	**CRI80, CRI90**	**<19**

Introduction

A range of recessed luminaires with mid-power LED modules using Multioptic® lens technology, specially designed for use with exposed grid ceilings. Myos-M 600x…

With the Myos-M Square 600x600, you choose architectural lighting that unites design and light quality. Designed for kantoren, zorg, education, public spaces, vrijetijdssector, the luminaire integrates neatly into the design and delivers comfortable, considered light. Thanks to its thoughtful detailing and high-quality finish, it is a choice that lasts for years — and makes your project look better.

Technical specifications

Mounting	**Inleg**
Application	**Kantoren, Zorg, Education, Public spaces, Vrijetijdssector**
Dimensions	**595x595mm**
Material	**Staal (behuizing)**
Optics	**MultiopticLens**
UGR	**<19**
IP class	**IP20 (boven) / IP20 (onder)**
CRI	**CRI80, CRI90**
CCT	**3000K, 4000K**
Control	**aan/uit, DALI-2, 1-10v, Casambi, On request**
Emergency lighting	**1-hour emergency power, 1 uur autonomie autotest**
Service life	**L90@50.000 uur**
Voltage / freq.	**220-240V, 50 / 60Hz**
Efficiency	**>140lm/W**
Photobiological safety	**IEC 62471: RG1 (low risk)**
Insulation class	**Class II**
Power factor	**>0.9**
Ambient temperature	**-20°C / +40°C**
Colour	**RAL9016, RAL9005, On request**
Options	**Attached to the luminaire, Remote driver, Optional, BST 14i2, Europlug, GST18i3, GST18i5 pastelblauw, On request, On the driver**
Brand	**Atomis**
Category	**Recessed & lay-in luminaires**

Technical drawings

Dimensions and line art — not to scale



Photometric drawing

Specification text

Myos-M square 600x600 is a recessed and lay-in luminaire from the Myos range by Atomis. The luminaire is lay-in, directed downward and fitted with a Multioptic lens. The range is intended for offices, healthcare, education, public spaces and leisure venues.

Information

Note

Specifications depend on the project and configuration. Always consult the current technical documentation.

This datasheet is compiled from structured product information held in the Atomis luminaire database. Specifications may vary per project configuration.

Atomis Architectural Lighting · atomislighting.com · The Netherlands

Generated on 8 November 2026