



ATOMIS

Myos-M 600x600

A range of recessed luminaires with mid-power LED modules using Multioptic® lens technology, specially designed for use with exposed grid ceilings. Myos-M 600x...

CATEGORY

Recessed & lay-in luminaires

MOUNTING

Ceiling-mounted

IP CLASS

IP20 (naar boven)/IP40 (naar beneden)

COLOUR TEMPERATURE

3000K, 4000K

CRI

CR180, CR190

UGR

<19

Introduction

A range of recessed luminaires with mid-power LED modules using Multioptic® lens technology, specially designed for use with exposed grid ceilings. Myos-M 600x...

With the Myos-M 600x600, you choose architectural lighting that unites design and light quality. Designed for hospitality, office, education, public spaces, the luminaire integrates neatly into the design and delivers comfortable, considered light. Thanks to its thoughtful detailing and high-quality finish, it is a choice that lasts for years — and makes your project look better.

Features

Can be seamlessly integrated into exposed grid ceilings

Architectural design

Fitted with 99 lenses (UGR < 16–19)

Technical specifications

Mounting	Ceiling-mounted
Application	Hospitality, Office, Education, Public spaces
Material	Acrylic, Steel
Optics	Multioptic® lens technology
UGR	<19
IP class	IP20 (naar boven)/IP40 (naar beneden)
CRI	CRI80, CRI90
CCT	3000K, 4000K
Control	1-10V dimmable, Casambi dimmable, DALI dimmable, Optional
Emergency lighting	1-hour emergency power, Optional, Optional 1-hour autonomy self-test
Efficiency	>140lm/W
Photobiological safety	IEC 62471: RG1 (low risk)
Insulation class	Class II
Power factor	>0.9
Ambient temperature	-20°C / +40°C
Options	Attached to the luminaire, Remote driver, Optional, BST 14i2, Europlug, GST18i3, GST18i5 pastelblauw, On request, On the driver
Brand	Atomis
Category	Recessed & lay-in luminaires

Technical drawings

Dimensions and line art — not to scale



Photometric drawing

Specification text

A range of recessed luminaires with mid-power LED modules using Multioptic® lens technology, specially designed for use with exposed grid ceilings. Myos-M 600x600 Multioptic® contains a set of 99 mid-power LEDs behind a decorative aperture mask. Each LED has an individual secondary lens for an excellent light distribution. The housing is made of steel, powder-coated RAL9016 or RAL9010 with a textured finish. - Can be seamlessly integrated into exposed grid ceilings - Architectural design - Fitted with 99 lenses (UGR < 16–19)

Information

Note

Specifications depend on the project and configuration. Always consult the current technical documentation.

This datasheet is compiled from structured product information based on XML source data and the current source page. Specifications may vary per project configuration.

Atomis Architectural Lighting · atomislighting.com · The Netherlands

Generated on 9 July 2026