



ATOMIS

# Myos MOS Multioptic® Suspension System

Myos-MOS Multioptic® Suspension System is an innovative pendant luminaire with mid-power LED modules using Multioptic® lens technology. It contains LED modules...

**CATEGORY**

**Pendant luminaires**

**MOUNTING**

**Pendant**

**IP CLASS**

**IP20 (naar boven)/IP40 (naar beneden)**

**COLOUR TEMPERATURE**

**3000K, 4000K**

**CRI**

**CR180, CR190**

**UGR**

**<19**

## Introduction

Myos-MOS Multioptic® Suspension System is an innovative pendant luminaire with mid-power LED modules using Multioptic® lens technology. It contains LED modules...

With the Myos MOS Multioptic® Suspension System, you choose architectural lighting that unites design and light quality. Designed for hospitality, office, education, public spaces, the luminaire integrates neatly into the design and delivers comfortable, considered light. Thanks to its thoughtful detailing and high-quality finish, it is a choice that lasts for years — and makes your project look better.

---

## Features

Excellent low-glare UGR < 19 task lighting in line with EN 12464-1 for use in offices

Finish in a decorative matt white or matt black textured coating

## Technical specifications

Mounting	<b>Pendant</b>
Application	<b>Hospitality, Office, Education, Public spaces</b>
Material	<b>Acrylic, Steel</b>
Optics	<b>Multioptic® lens technology</b>
UGR	<b>&lt;19</b>
IP class	<b>IP20 (naar boven)/IP40 (naar beneden)</b>
CRI	<b>CRI80, CRI90</b>
CCT	<b>3000K, 4000K</b>
Control	<b>1-10V dimmable, Casambi dimmable, DALI dimmable, Optional</b>
Emergency lighting	<b>1-hour emergency power, Optional, Optional 1-hour autonomy self-test</b>
Efficiency	<b>&gt;140lm/W</b>
Photobiological safety	<b>IEC 62471: RG1 (low risk)</b>
Insulation class	<b>Class I, Class II</b>
Power factor	<b>&gt;0.9</b>
Ambient temperature	<b>-20°C / +40°C</b>
Options	<b>Integrated, Optional, Cable, On request, On the driver</b>
Brand	<b>Atomis</b>
Category	<b>Pendant luminaires</b>

## Product photos

Atmosphere and product images





## Specification text

Myos-MOS Multioptic® Suspension System is an innovative pendant luminaire with mid-power LED modules using Multi-optic® lens technology. It contains LED modules of 33 power LEDs each, behind a decorative aperture mask. All modules can be configured as desired—up-light, downlight, or both in a single luminaire module. Thanks to the luminaire's linkable design, it is ideally suited to spaces where no suspended ceiling is available. - Excellent low-glare UGR < 19 task lighting in line with EN 12464-1 for use in offices - Finish in a decorative matt white or matt black textured coating

## Information

### Note

Specifications depend on the project and configuration. Always consult the current technical documentation.

This datasheet is compiled from structured product information based on XML source data and the current source page. Specifications may vary per project configuration.