

## ATOMIS

# Myos Multiple Pendant

Myos Multiple Pendant is a suspended luminaire from the Myos range by Atomis. The luminaire is suspended, directed downward or up/down and fitted with a Multioptic lens. The range is intended for offices, healthcare, education, public spaces and leisure venues.

## CATEGORY

**Pendant luminaires**

## MOUNTING

**Pendant**

## IP CLASS

**IP20 (boven) / IP20 (onder)**

## COLOUR TEMPERATURE

**3000K, 4000K**

## CRI

**CRI80, CRI90**

## UGR

**<19**

## Introduction

Myos Multiple Pendant is a suspended luminaire from the Myos range by Atomis. The luminaire is suspended, directed downward or up/down and fitted with a Multioptic lens. The range is intended for offices, healthcare, education, public spaces and leisure venues.

With the Myos Multiple Pendant, you choose architectural lighting that unites design and light quality. Designed for kantoren, zorg, education, public spaces, vrijetijdssector, the luminaire integrates neatly into the design and delivers comfortable, considered light. Thanks to its thoughtful detailing and high-quality finish, it is a choice that lasts for years — and makes your project look better.

## Technical specifications

|                        |                                                                  |
|------------------------|------------------------------------------------------------------|
| Mounting               | <b>Pendant</b>                                                   |
| Application            | <b>Kantoren, Zorg, Education, Public spaces, Vrijtjidssector</b> |
| Dimensions             | <b>On request</b>                                                |
| Material               | <b>Staal (behuizing)</b>                                         |
| Optics                 | <b>MultiopticLens</b>                                            |
| UGR                    | <b>&lt;19</b>                                                    |
| IP class               | <b>IP20 (boven) / IP20 (onder)</b>                               |
| CRI                    | <b>CRI80, CRI90</b>                                              |
| CCT                    | <b>3000K, 4000K</b>                                              |
| Control                | <b>aan/uit, DALI-2, 1-10v, Casambi, On request</b>               |
| Emergency lighting     | <b>1 uur noodtroom, 1 uur autonomie autotest</b>                 |
| Voltage / freq.        | <b>220-240V, 50 / 60Hz</b>                                       |
| Photobiological safety | <b>IEC 62471: RG1 (low risk)</b>                                 |
| Insulation class       | <b>Class I</b>                                                   |
| Power factor           | <b>&gt;0.9</b>                                                   |
| Ambient temperature    | <b>-20°C / +40°C</b>                                             |
| Colour                 | <b>RAL9016, RAL9005, On request</b>                              |
| Brand                  | <b>Atomis</b>                                                    |
| Category               | <b>Pendant luminaires</b>                                        |

## Specification text

Myos Multiple Pendant is a suspended luminaire from the Myos range by Atomis. The luminaire is suspended, directed downward or up/down and fitted with a Multioptic lens. The range is intended for offices, healthcare, education, public spaces and leisure venues.

## Information

### Note

Specifications depend on the project and configuration. Always consult the current technical documentation.

This datasheet is compiled from structured product information held in the Atomis luminaire database. Specifications may vary per project configuration.

Atomis Architectural Lighting · atomislighting.com · The Netherlands

Generated on 21 July 2026