



ATOMIS

Myos-S2 Multioptic® Up/Down

Myos-S2 Multioptic® Up/Down is an innovative pendant luminaire with mid-power LED modules using Multioptic® lens technology. It contains 5 modules of 33 power ...

CATEGORY

Pendant luminaires

MOUNTING

Pendant

IP CLASS

IP20 (naar boven)/IP40 (naar beneden)

COLOUR TEMPERATURE

3000K, 4000K

CRI

CR180, CR190

UGR

<19

Introduction

Myos-S2 Multioptic® Up/Down is an innovative pendant luminaire with mid-power LED modules using Multioptic® lens technology. It contains 5 modules of 33 power ...

With the Myos-S2 Multioptic® Up/Down, you choose architectural lighting that unites design and light quality. Designed for hospitality, office, education, public spaces, the luminaire integrates neatly into the design and delivers comfortable, considered light. Thanks to its thoughtful detailing and high-quality finish, it is a choice that lasts for years — and makes your project look better.

Features

Elegant, ultra-thin design of just 11 mm high

Excellent low-glare UGR < 19 task lighting in line with EN 12464-1 for use in offices

Finish in a decorative matt white or matt black textured coating

Technical specifications

Mounting	Pendant
Application	Hospitality, Office, Education, Public spaces
Material	Acrylic, Steel
Optics	Multioptic® lens technology
UGR	<19
IP class	IP20 (naar boven)/IP40 (naar beneden)
CRI	CRI80, CRI90
CCT	3000K, 4000K
Control	1-10V dimmable, Casambi dimmable, DALI dimmable, Optional
Emergency lighting	1-hour emergency power, Optional, Optional 1-hour autonomy self-test
Efficiency	>140lm/W
Photobiological safety	IEC 62471: RG1 (low risk)
Insulation class	Class I, Class II
Power factor	>0.9
Ambient temperature	-20°C / +40°C
Options	Remote driver, Optional, Cable, On request, On the driver
Brand	Atomis
Category	Pendant luminaires

Product photos

Atmosphere and product images



Specification text

Myos-S2 Multioptic® Up/Down is an innovative pendant luminaire with mid-power LED modules using Multioptic® lens technology. It contains 5 modules of 33 power LEDs each, behind a decorative aperture mask. Three modules are directed downward for effective lighting of the work area and two modules are directed upward for indirect lighting. - Elegant, ultra-thin design of just 11 mm high - Excellent low-glare UGR < 19 task lighting in line with EN 12464-1 for use in offices - Finish in a decorative matt white or matt black textured coating

Information

Note

Specifications depend on the project and configuration. Always consult the current technical documentation.

This datasheet is compiled from structured product information based on XML source data and the current source page. Specifications may vary per project configuration.

Atomis Architectural Lighting · atomislighting.com · The Netherlands

Generated on 10 July 2026