



ATOLUX

Oxo 35-L

Oxo 35-L is a climate ceiling and baffle luminaire from the Oxo range by Atolux. The luminaire is lay-in, fully adjustable and fitted with Lens. The range is intended for offices, museums, public spaces, leisure venues and retail.

CATEGORY

Climate ceiling luminaires, Baffle luminaires

MOUNTING

Inleg

IP CLASS

IP20 (boven) / IP20 (onder)

COLOUR TEMPERATURE

3000K, 4000K

CRI

CRI90

Introduction

Oxo 35-L is a climate ceiling and baffle luminaire from the Oxo range by Atolux. The luminaire is lay-in, fully adjustable and fitted with Lens. The range is intended for offices, museums, public spaces, leisure venues and retail.

With the Oxo 35-L, you choose architectural lighting that unites design and light quality. Designed for kantoren, musea, public spaces, vrijetijdssector, retail, the luminaire integrates neatly into the design and delivers comfortable, considered light. Thanks to its thoughtful detailing and high-quality finish, it is a choice that lasts for years — and makes your project look better.

Technical specifications

Mounting	Inleg
Application	Kantoren, Musea, Public spaces, Vrijetijdssector, Retail
Dimensions	35mm
Material	Aluminium (behuizing)
Optics	Lens
IP class	IP20 (boven) / IP20 (onder)
CRI	CRI90
CCT	3000K, 4000K
Control	aan/uit, DALI-2, 1-10v, Casambi, On request
Emergency lighting	1-hour emergency power, Optional, Optional 1-hour autonomy self-test
Voltage / freq.	220-240V, 50 / 60Hz
Efficiency	>70lm/W
Photobiological safety	IEC 62471: RG1 (low risk)
Insulation class	Class II
Power factor	>0.9
Ambient temperature	-20°C / +40°C
Colour	RAL9016, RAL9005, On request
Options	93 100 100 100 100, BST 14i2, Europlug, GST18i3, GST18i5 pastelblauw, L90B50@60, 000h (Tq 25°C), Remote driver, N/A, On request, On the driver, Adjustable, Round, SDCM=2
Brand	Atolux
Category	Climate ceiling luminaires, Baffle luminaires

Specification text

Oxo 35-L is a climate ceiling and baffle luminaire from the Oxo range by Atolux. The luminaire is lay-in, fully adjustable and fitted with Lens. The range is intended for offices, museums, public spaces, leisure venues and retail.

Information

Note

Specifications depend on the project and configuration. Always consult the current technical documentation.

This datasheet is compiled from structured product information held in the Atomis luminaire database. Specifications may vary per project configuration.

Atomis Architectural Lighting · atomislighting.com · The Netherlands

Generated on 31 August 2026