


ATOLUX

# Refurbishment Metronome

Refurbishment Metronome is a linear LED luminaire fitted with a row of 12 lenses decoratively recessed behind a louvre grille. The luminaire combines functiona…

| | | |
|---|---|---|
| CATEGORY<br>**Refurbishment armaturen** | MOUNTING<br>**Recessed** | IP CLASS<br>**IP20 (boven) / IP20 (onder)** |
| COLOUR TEMPERATURE<br>**2700K, 3000K, 4000K, Tunable white, op aanvraag** | CRI<br>**CRI80, CRI90** | UGR<br>**<19** |

## Introduction

Refurbishment Metronome is a linear LED luminaire fitted with a row of 12 lenses decoratively recessed behind a louvre grille. The luminaire combines functiona…

With the Track-RF Refurbishment, you choose architectural lighting that unites design and light quality. Designed for kantoren, zorg, education, public spaces, vrijetijdssector, the luminaire integrates neatly into the design and delivers comfortable, considered light. Thanks to its thoughtful detailing and high-quality finish, it is a choice that lasts for years — and makes your project look better.

# Technical specifications

| | |
|---|---|
| Mounting | **Recessed** |
| Application | **Kantoren, Zorg, Education, Public spaces, Vrijetijdssector** |
| Dimensions | **On request** |
| Material | **Staal (behuizing)** |
| Optics | **Lens met Louver** |
| UGR | **<19** |
| IP class | **IP20 (boven) / IP20 (onder)** |
| CRI | **CRI80, CRI90** |
| CCT | **2700K, 3000K, 4000K, Tunable white, On request** |
| Control | **aan/uit, DALI-2, 1-10v, Casambi, On request** |
| Emergency lighting | **1-hour emergency power, 1 uur autonomie autotest** |
| Service life | **L90@50.000 uur** |
| Voltage / freq. | **220-240V, 50 / 60Hz** |
| Efficiency | **>140lm/W** |
| Photobiological safety | **IEC 62471: RG1 (low risk)** |
| Insulation class | **Class II** |
| Power factor | **>0.9** |
| Ambient temperature | **-20°C / +40°C** |
| Colour | **RAL9016, RAL9005, On request** |
| Options | **93 100 100 100 100, Attached to the luminaire, BST 14i2, Europlug, GST18i3, GST18i5 pastelblauw, L90B50@60, 000h (Tq 25°C), Remote driver, Downward, On request, On the driver, Optional, Rectangular, SDCM=3** |
| Brand | **Atolux** |
| Category | **Refurbishment armaturen** |

# Product photos

Atmosphere and product images



## Specification text

Metronome-RF Refurbishment is a refurbishment and retrofit luminaire from the Metronome range by Atomis. The luminaire is recessed, directed downward and fitted with a lens with louvre. The range is intended for offices, healthcare, education, public spaces and leisure venues.

# Information

Note

Specifications depend on the project and configuration. Always consult the current technical documentation.

This datasheet is compiled from structured product information held in the Atomis luminaire database. Specifications may vary per project configuration.

Atomis Architectural Lighting · atomislighting.com · The Netherlands

Generated on 23 November 2026