



ATOMIS

Ultralight-SAPP

Ultralight-SAPP is an elegant, slim LED luminaire fitted with a row of mid-power LEDs, each with its own lens and louvre. This luminaire is specially designed ...

CATEGORY

Climate ceiling luminaires, Baffle luminaires

MOUNTING

Recessed

IP CLASS

IP20 (naar boven)/IP40 (naar beneden)

COLOUR TEMPERATURE

2700K, 3000K, 3500K, 4000K, Tunable White

CRI

CR180, CR190

UGR

<19

Introduction

Ultralight-SAPP is an elegant, slim LED luminaire fitted with a row of mid-power LEDs, each with its own lens and louvre. This luminaire is specially designed ...

With the Ultralight-SAPP, you choose architectural lighting that unites design and light quality. Designed for hospitality, office, education, public spaces, the luminaire integrates neatly into the design and delivers comfortable, considered light. Thanks to its thoughtful detailing and high-quality finish, it is a choice that lasts for years — and makes your project look better.

Features

Elegant, slim design for use in linear baffle ceilings

Excellent low-glare task lighting in line with EN 12464-1 for use in offices

Available in a matt white or matt black textured coating

Technical specifications

Mounting	Recessed
Application	Hospitality, Office, Education, Public spaces
Material	Acrylic, Steel
Optics	Lens and louvre
UGR	<19
IP class	IP20 (naar boven)/IP40 (naar beneden)
CRI	CRI80, CRI90
CCT	2700K, 3000K, 3500K, 4000K, Tunable White
Control	1-10V dimmable, Casambi dimmable, DALI dimmable, Optional
Emergency lighting	1-hour emergency power, Optional, Optional 1-hour autonomy self-test
Efficiency	>140lm/W
Photobiological safety	IEC 62471: RG1 (low risk)
Insulation class	Class II
Power factor	>0.9
Ambient temperature	-20°C / +40°C
Options	220-240V, 50 / 60Hz, 93 100 100 100 100, BST 14i2, Europlug, GST18i3, GST18i5 pastelblauw, L90B50@60, 000h (Tq 25°C), Remote driver, N/A, Downward, On request, On the driver, Rectangular, SDCM=3
Brand	Atomis
Category	Climate ceiling luminaires, Baffle luminaires

Product photos

Atmosphere and product images



Specification text

Ultralight-SAPP is an elegant, slim LED luminaire fitted with a row of mid-power LEDs, each with its own lens and louvre. This luminaire is specially designed for use in linear baffle ceilings. - Elegant, slim design for use in linear baffle ceilings - Excellent low-glare task lighting in line with EN 12464-1 for use in offices - Available in a matt white or matt black textured coating

Information

Note

Specifications depend on the project and configuration. Always consult the current technical documentation.

This datasheet is compiled from structured product information based on XML source data and the current source page. Specifications may vary per project configuration.

Atomis Architectural Lighting · atomislighting.com · The Netherlands

Generated on 10 July 2026