

ATOLUX

Vector-125 Black

Vector-125 Black is a downlight and recessed spotlight from the Vector range by Atolux. The luminaire is recessed, directed downward and fitted with a lens with louvre. The range is intended for offices, museums, healthcare, education, public spaces, leisure venues and retail.

CATEGORY
Downlights & recessed spots

MOUNTING
Recessed

IP CLASS
IP20 (boven) / IP20 (onder)

COLOUR TEMPERATURE
3000K, 4000K

CRI
CRI90

Introduction

Vector-125 Black is a downlight and recessed spotlight from the Vector range by Atolux. The luminaire is recessed, directed downward and fitted with a lens with louvre. The range is intended for offices, museums, healthcare, education, public spaces, leisure venues and retail.

With the Vector-125 Black, you choose architectural lighting that unites design and light quality. Designed for kantoren, musea, zorg, education, public spaces, vrijetijdssector, retail, the luminaire integrates neatly into the design and delivers comfortable, considered light. Thanks to its thoughtful detailing and high-quality finish, it is a choice that lasts for years — and makes your project look better.

Technical specifications

Mounting	**Recessed**
Application	**Kantoren, Musea, Zorg, Education, Public spaces, Vrijetijdssector, Retail**
Dimensions	**31x126mm**
Material	**Aluminium (behuizing)**
Optics	**Lens met Louver**
IP class	**IP20 (boven) / IP20 (onder)**
CRI	**CRI90**
CCT	**3000K, 4000K**
Control	**aan/uit, DALI-2**
Service life	**L90@100.000 uur**
Voltage / freq.	**220-240V, 50 / 60Hz**
Efficiency	**70**
Photobiological safety	**IEC 62471: RG1 (low risk)**
Insulation class	**Class II**
Power factor	**>0.9**
Ambient temperature	**-20°C / +40°C**
Colour	**RAL9016**
Brand	**Atolux**
Category	**Downlights & recessed spots**

Product photos

Atmosphere and product images



Specification text

Vector-125 Black is a downlight and recessed spotlight from the Vector range by Atolux. The luminaire is recessed, directed downward and fitted with a lens with louvre. The range is intended for offices, museums, healthcare, education, public spaces, leisure venues and retail.

Information

Note

Specifications depend on the project and configuration. Always consult the current technical documentation.

This datasheet is compiled from structured product information held in the Atomis luminaire database. Specifications may vary per project configuration.

Atomis Architectural Lighting · atomislighting.com · The Netherlands

Generated on 31 October 2026