



ATOMIS

Zumo 60-C Vario White

Zumo 60-C Vario is the surface-mounted version of the Zumo zoom spot. The adjustable LED spot is mounted directly onto the ceiling and offers an adjustable beam via a zoom lens, excellent colour rendering (CRI 90-97) and high colour consistency (SDCM 2). Available in 3000K, 4000K and tunable white, dimmable via DALI-2, 1-10V and Casambi. Ideal for accent and object lighting in offices, museums, public spaces and the leisure sector.

CATEGORY

Surface-mounted luminaires

MOUNTING

Surface-mounted

IP CLASS

IP20 (boven) / IP20 (onder)

COLOUR TEMPERATURE

3000K, 4000K, Tunable white

CRI

CRI90, CRI97

Introduction

Zumo 60-C Vario is the surface-mounted version of the Zumo zoom spot. The adjustable LED spot is mounted directly onto the ceiling and offers an adjustable beam via a zoom lens, excellent colour rendering (CRI 90-97) and high colour consistency (SDCM 2). Available in 3000K, 4000K and tunable white, dimmable via DALI-2, 1-10V and Casambi. Ideal for accent and object lighting in offices, museums, public spaces and the leisure sector.

With the Zumo 60-C Vario White, you choose architectural lighting that unites design and light quality. Designed for kantoren, musea, public spaces, vrijetijdssector, the luminaire integrates neatly into the design and delivers comfortable, considered light. Thanks to its thoughtful detailing and high-quality finish, it is a choice that lasts for years — and makes your project look better.

Technical specifications

Mounting	Surface-mounted
Application	Kantoren, Musea, Public spaces, Vrijetijdssector
Dimensions	55x140mm
Material	Aluminium (behuizing)
Optics	Zoom lens
IP class	IP20 (boven) / IP20 (onder)
CRI	CRI90, CRI97
CCT	3000K, 4000K, Tunable white
Control	aan/uit, DALI-2, 1-10v, Casambi, On request
Voltage / freq.	220-240V, 50 / 60Hz
Photobiological safety	IEC 62471: RG1 (low risk)
Insulation class	Class II
Power factor	>0.9
Ambient temperature	-20°C / +40°C
Colour	RAL9016
Brand	Atomis
Category	Surface-mounted luminaires

Product photos

Atmosphere and product images



Specification text

Zumo 60-C Vario is the surface-mounted version of the Zumo zoom spot. The adjustable LED spot is mounted directly onto the ceiling and offers an adjustable beam via a zoom lens, excellent colour rendering (CRI 90-97) and high colour consistency (SDCM 2). Available in 3000K, 4000K and tunable white, dimmable via DALI-2, 1-10V and Casambi. Ideal for accent and object lighting in offices, museums, public spaces and the leisure sector.

Information

Note

Specifications depend on the project and configuration. Always consult the current technical documentation.

This datasheet is compiled from structured product information based on XML source data and the current source page. Specifications may vary per project configuration.

Atomis Architectural Lighting · atomislighting.com · The Netherlands

Generated on 17 September 2026