



## ATOMIS

# Zumo 60-R Vario White

Zumo 60-R Vario is the recessed version of the Zumo zoom spot. The adjustable LED spot is recessed into the ceiling and offers an adjustable beam via a zoom lens, excellent colour rendering (CRI 90-97) and high colour consistency (SDCM 2). Available in 3000K, 4000K and tunable white, dimmable via DALI-2, 1-10V and Casambi. Ideal for accent and object lighting in offices, museums, public spaces and the leisure sector.

### CATEGORY

**Downlights & recessed spots**

### MOUNTING

**Recessed**

### IP CLASS

**IP20 (boven) / IP20 (onder)**

### COLOUR TEMPERATURE

**3000K, 4000K, Tunable white**

### CRI

**CRI90, CRI97**

## Introduction

Zumo 60-R Vario is the recessed version of the Zumo zoom spot. The adjustable LED spot is recessed into the ceiling and offers an adjustable beam via a zoom lens, excellent colour rendering (CRI 90-97) and high colour consistency (SDCM 2). Available in 3000K, 4000K and tunable white, dimmable via DALI-2, 1-10V and Casambi. Ideal for accent and object lighting in offices, museums, public spaces and the leisure sector.

With the Zumo 60-R Vario White, you choose architectural lighting that unites design and light quality. Designed for kantoren, musea, public spaces, vrijetijdssector, the luminaire integrates neatly into the design and delivers comfortable, considered light. Thanks to its thoughtful detailing and high-quality finish, it is a choice that lasts for years — and makes your project look better.

## Technical specifications

|                        |                                                         |
|------------------------|---------------------------------------------------------|
| Mounting               | <b>Recessed</b>                                         |
| Application            | <b>Kantoren, Musea, Public spaces, Vrijetijdssector</b> |
| Dimensions             | <b>55x140mm</b>                                         |
| Material               | <b>Aluminium (behuizing)</b>                            |
| Optics                 | <b>Zoom lens</b>                                        |
| IP class               | <b>IP20 (boven) / IP20 (onder)</b>                      |
| CRI                    | <b>CRI90, CRI97</b>                                     |
| CCT                    | <b>3000K, 4000K, Tunable white</b>                      |
| Control                | <b>aan/uit, DALI-2, 1-10v, Casambi, On request</b>      |
| Voltage / freq.        | <b>220-240V, 50 / 60Hz</b>                              |
| Photobiological safety | <b>IEC 62471: RG1 (low risk)</b>                        |
| Insulation class       | <b>Class II</b>                                         |
| Power factor           | <b>&gt;0.9</b>                                          |
| Ambient temperature    | <b>-20°C / +40°C</b>                                    |
| Colour                 | <b>RAL9016</b>                                          |
| Brand                  | <b>Atomis</b>                                           |
| Category               | <b>Downlights &amp; recessed spots</b>                  |

## Product photos

Atmosphere and product images



## Specification text

Zumo 60-R Vario is the recessed version of the Zumo zoom spot. The adjustable LED spot is recessed into the ceiling and offers an adjustable beam via a zoom lens, excellent colour rendering (CRI 90-97) and high colour consistency (SDCM 2). Available in 3000K, 4000K and tunable white, dimmable via DALI-2, 1-10V and Casambi. Ideal for accent and object lighting in offices, museums, public spaces and the leisure sector.

## Information

### Note

Specifications depend on the project and configuration. Always consult the current technical documentation.

This datasheet is compiled from structured product information based on XML source data and the current source page. Specifications may vary per project configuration.

Atomis Architectural Lighting · atomislighting.com · The Netherlands

Generated on 17 September 2026