



ATOMIS

Zumo 60 Vario white

Zumo 60 Vario is a zoomable LED spot for standard 3-phase track. The spot features a powerful LED with a high colour rendering index (CRI > 97). The beam can b...

CATEGORY

Track luminaires

MOUNTING

Track

IP CLASS

IP20 (naar boven)/IP40 (naar beneden)

COLOUR TEMPERATURE

2700K, 3000K, 3500K, 4000K, Tunable White

CRI

CRI97

UGR

n-v-t-

Introduction

Zumo 60 Vario is a zoomable LED spot for standard 3-phase track. The spot features a powerful LED with a high colour rendering index (CRI > 97). The beam can b...

With the Zumo 60 Vario white, you choose architectural lighting that unites design and light quality. Designed for exhibition spaces, hospitality, office, education, public spaces, retail, the luminaire integrates neatly into the design and delivers comfortable, considered light. Thanks to its thoughtful detailing and high-quality finish, it is a choice that lasts for years — and makes your project look better.

Features

Compact design LED spot (ø60 mm) for standard track

High CRI (> 97) colour rendering index

Continuously adjustable beam from 10° spot to 50° wide flood

Flicker-free dimming (in accordance with IEEE 1789) at the spot

Particularly suitable for lighting galleries, museums and exhibition spaces

Technical specifications

Mounting	Track
Application	Exhibition spaces, Hospitality, Office, Education, Public spaces, Retail
Material	Acrylic, Aluminium
Optics	Zoom lens
UGR	n-v-t-
IP class	IP20 (naar boven)/IP40 (naar beneden)
CRI	CRI97
CCT	2700K, 3000K, 3500K, 4000K, Tunable White
Control	1-10V dimmable, Casambi dimmable, DALI dimmable, Optional
Emergency lighting	N/A
Efficiency	>85lm/W
Photobiological safety	IEC 62471: RG1 (low risk)
Insulation class	Class I
Power factor	>0.9
Ambient temperature	-20°C / +40°C
Options	220-240V, 50 / 60Hz, 93 100 100 100 100, Phase track, Integrated, L90B50@60, 000h (Tq 25°C), N/A, On request, Adjustable, Round, SDCM=2
Brand	Atomis
Category	Track luminaires

Product photos

Atmosphere and product images



Specification text

Zumo 60 Vario is a zoomable LED spot for standard 3-phase track. The spot features a powerful LED with a high colour rendering index (CRI > 97). The beam can be continuously adjusted from a 10° spot to a 50° wide flood simply by turning the zoom lens. Zumo 60 Vario spots are particularly suitable for lighting galleries, museums and art exhibitions. - Compact design LED spot (ø60 mm) for standard track - High CRI (> 97) colour rendering index - Continuously adjustable beam from 10° spot to 50° wide flood - Flicker-free dimming (in accordance with IEEE 1789) at the spot - Particularly suitable for lighting galleries, museums and exhibition spaces

Information

Note

Specifications depend on the project and configuration. Always consult the current technical documentation.

This datasheet is compiled from structured product information based on XML source data and the current source page. Specifications may vary per project configuration.

Atomis Architectural Lighting · atomislighting.com · The Netherlands

Generated on 9 July 2026