



ATOMIS

Zumo 80 contour black

Zumo 80 contour is an LED track spotlight with a framing projector, for standard 3-circuit and 5-circuit track systems. Its shapeable optic lets the beam follow the outline of...

CATEGORY

Track luminaires

MOUNTING

Track

IP CLASS

IP20 (boven) / IP20 (onder)

COLOUR TEMPERATURE

3000K, 4000K

CRI

CRI90, CRI97

Introduction

Zumo 80 contour is an LED track spotlight with a framing projector, for standard 3-circuit and 5-circuit track systems. Its shapeable optic lets the beam follow the outline of...

With the Zumo 80 contour Black, you choose architectural lighting that unites design and light quality. Designed for musea, vrijetijdssector, the luminaire integrates neatly into the design and delivers comfortable, considered light. Thanks to its thoughtful detailing and high-quality finish, it is a choice that lasts for years — and makes your project look better.

Features

the light stops where the object stops. In a museum setting that avoids spill light on walls and floors, and with it the visual restlessness that comes from it. || The Zumo 80 contour has a shapeable optic and is fully adjustable, so the spotlight can still be aimed after installation. The luminaire measures 75 by 215 mm and is round, made of aluminium with a polycarbonate optic. || ## Colour that holds up || For spaces where colour rendering carries weight, the spotlight is available with CRI90 or CRI97. Colour consistency is fixed at SDCM=2, so luminaires show no visible colour difference between them

with a row of spotlights above the same wall, it is precisely that mutual deviation that stands out. The luminaire is recognised under ANSI/IES TM-30-18, the method that describes colour rendering more accurately than the CRI value alone. Available in 3000K and 4000K. || ## Control and installation || The driver is integrated into the luminaire. Control is available via on/off, DALI-2, 1-10V or Casambi; other versions are available on request. Flicker stays below 3 per cent, which matters in spaces where filming or photography takes place. Connection is made with a 3-circuit or 5-circuit track adapter. || The luminaire is built to insulation class II, with IP20 protection and photobiological safety compliant with IEC 62471 RG1 (low risk). The operating range runs from -20 to +40 degrees Celsius. The product carries a five-year warranty.

Technical specifications

Mounting	Track
Application	Musea, Vrijetijdssector
Dimensions	75x215mm
Material	Aluminium (behuizing)
Optics	Vormbaar optiek
IP class	IP20 (boven) / IP20 (onder)
CRI	CRI90, CRI97
CCT	3000K, 4000K
Control	aan/uit, DALI-2, 1-10v, Casambi, On request
Voltage / freq.	220-240V, 50 / 60Hz
Photobiological safety	IEC 62471: RG1 (low risk)
Insulation class	Class II
Power factor	>0.9
Ambient temperature	-20°C / +40°C
Colour	RAL9005
Brand	Atomis
Category	Track luminaires

Product photos

Atmosphere and product images



Specification text

Atomis Zumo 80 contour black LED track spotlight. Round, adjustable track spotlight of 75x215 mm with framing projector and shapeable optic, for use on 3-circuit and 5-circuit track systems. Aluminium body with polycarbonate optic in black (RAL9005), insulation class II, IP20, colour consistency SDCM=2 and photobiological safety compliant with IEC 62471 RG1 (low risk). Available in 3000K and 4000K with CRI90 or CRI97, recognised under ANSI/IES TM-30-18.

Information

Note

Specifications depend on the project and configuration. Always consult the current technical documentation.

This datasheet is compiled from structured product information based on XML source data and the current source page. Specifications may vary per project configuration.

Atomis Architectural Lighting · atomislighting.com · The Netherlands

Generated on 31 August 2026