

ATOMIS

Zumo 80 contour white

Zumo 80 contour is an LED track spotlight with a framing projector, for standard 3-circuit and 5-circuit track systems. Its shapeable optic lets the beam follow the outline of…

CATEGORY
Track luminaires

MOUNTING
Track

IP CLASS
IP20 (boven) / IP20 (onder)

COLOUR TEMPERATURE
3000K, 4000K

CRI
CRI90, CRI97

Introduction

Zumo 80 contour is an LED track spotlight with a framing projector, for standard 3-circuit and 5-circuit track systems. Its shapeable optic lets the beam follow the outline of…

With the Zumo 80 contour White, you choose architectural lighting that unites design and light quality. Designed for musea, vrijetijdssector, the luminaire integrates neatly into the design and delivers comfortable, considered light. Thanks to its thoughtful detailing and high-quality finish, it is a choice that lasts for years — and makes your project look better.

Technical specifications

Mounting	**Track**
Application	**Musea, Vrijetijdssector**
Dimensions	**75x215mm**
Material	**Aluminium (behuizing)**
Optics	**Vormbaar optiek**
IP class	**IP20 (boven) / IP20 (onder)**
CRI	**CRI90, CRI97**
CCT	**3000K, 4000K**
Control	**aan/uit, DALI-2, 1-10v, Casambi, On request**
Service life	**L90@100.000 uur**
Voltage / freq.	**220-240V, 50 / 60Hz**
Photobiological safety	**IEC 62471: RG1 (low risk)**
Insulation class	**Class II**
Power factor	**>0.9**
Ambient temperature	**-20°C / +40°C**
Colour	**RAL9016**
Brand	**Atomis**
Category	**Track luminaires**

Product photos

Atmosphere and product images



Specification text

Atomis Zumo 80 contour white LED track spotlight. Round, adjustable track spotlight of 75x215 mm with framing projector and shapeable optic, for use on 3-circuit and 5-circuit track systems. Aluminium body with polycarbonate optic in white (RAL9016), insulation class II, IP20, colour consistency SDCM=2 and photobiological safety compliant with IEC 62471 RG1 (low risk). Available in 3000K and 4000K with CRI90 or CRI97, recognised under ANSI/IES TM-30-18.

Information

Note

Specifications depend on the project and configuration. Always consult the current technical documentation.

This datasheet is compiled from structured product information based on XML source data and the current source page. Specifications may vary per project configuration.

Atomis Architectural Lighting · atomislighting.com · The Netherlands

Generated on 30 October 2026