

ATOMIS

Zumo 90 Vario white

Zumo 90 Vario is a zoomable LED spot for standard 3-phase track. The spot features a powerful LED with a high colour rendering index (CRI > 97). The beam can b…

CATEGORY
Track luminaires

MOUNTING
Track

IP CLASS
IP20 (boven) / IP20 (onder)

COLOUR TEMPERATURE
3000K, 4000K, Tunable white

CRI
CRI90, CRI97

Introduction

Zumo 90 Vario is a zoomable LED spot for standard 3-phase track. The spot features a powerful LED with a high colour rendering index (CRI > 97). The beam can b…

With the Zumo 90 Vario White, you choose architectural lighting that unites design and light quality. Designed for kantoren, musea, public spaces, vrijetijdssector, the luminaire integrates neatly into the design and delivers comfortable, considered light. Thanks to its thoughtful detailing and high-quality finish, it is a choice that lasts for years — and makes your project look better.

Features

- Can be used on standard high-voltage track
- High CRI (> 97) colour rendering index
- Continuously adjustable beam from 12° spot to 55° wide flood
- Flicker-free dimming (in accordance with IEEE 1789) at the spot
- Particularly suitable for lighting galleries, museums and exhibition spaces

Technical specifications

Mounting	**Track**
Application	**Kantoren, Musea, Public spaces, Vrijetijdssector**
Dimensions	**90x192mm**
Material	**Aluminium (behuizing)**
Optics	**Zoom lens**
IP class	**IP20 (boven) / IP20 (onder)**
CRI	**CRI90, CRI97**
CCT	**3000K, 4000K, Tunable white**
Control	**aan/uit, DALI-2, 1-10v, Casambi, On request**
Service life	**L90@100.000 uur**
Voltage / freq.	**220-240V, 50 / 60Hz**
Photobiological safety	**IEC 62471: RG1 (low risk)**
Insulation class	**Class II**
Power factor	**>0.9**
Ambient temperature	**-20°C / +40°C**
Colour	**RAL9016**
Brand	**Atomis**
Category	**Track luminaires**

Product photos

Atmosphere and product images







Specification text

Zumo 90 Vario is a zoomable LED spot for standard 3-phase track. The spot features a powerful LED with a high colour rendering index (CRI > 97). The beam can be continuously adjusted from a 12° spot to a 55° wide flood simply by turning the zoom lens. Zumo 90 Vario spots are particularly suitable for lighting galleries, museums and art exhibitions. - Can be used on standard high-voltage track - High CRI (> 97) colour rendering index - Continuously adjustable beam from 12° spot to 55° wide flood - Flicker-free dimming (in accordance with IEEE 1789) at the spot - Particularly suitable for lighting galleries, museums and exhibition spaces

Information

Note

Specifications depend on the project and configuration. Always consult the current technical documentation.

This datasheet is compiled from structured product information based on XML source data and the current source page. Specifications may vary per project configuration.

Atomis Architectural Lighting · atomislighting.com · The Netherlands

Generated on 27 November 2026