



**ATOMIS**

# Zumo 90 Vario white

Zumo 90 Vario is a zoomable LED spot for standard 3-phase track. The spot features a powerful LED with a high colour rendering index (CRI > 97). The beam can b...

**CATEGORY**

**Track luminaires**

**MOUNTING**

**Track**

**IP CLASS**

**IP20 (naar boven)/IP40 (naar beneden)**

**COLOUR TEMPERATURE**

**2700K, 3000K, 3500K, 4000K, Tunable White**

**CRI**

**CRI97**

**UGR**

**n-v-t-**

## Introduction

Zumo 90 Vario is a zoomable LED spot for standard 3-phase track. The spot features a powerful LED with a high colour rendering index (CRI > 97). The beam can b...

With the Zumo 90 Vario white, you choose architectural lighting that unites design and light quality. Designed for exhibition spaces, hospitality, office, education, public spaces, retail, the luminaire integrates neatly into the design and delivers comfortable, considered light. Thanks to its thoughtful detailing and high-quality finish, it is a choice that lasts for years — and makes your project look better.

---

## Features

- Can be used on standard high-voltage track
- High CRI (> 97) colour rendering index
- Continuously adjustable beam from 12° spot to 55° wide flood
- Flicker-free dimming (in accordance with IEEE 1789) at the spot
- Particularly suitable for lighting galleries, museums and exhibition spaces

## Technical specifications

Mounting	<b>Track</b>
Application	<b>Exhibition spaces, Hospitality, Office, Education, Public spaces, Retail</b>
Material	<b>Acrylic, Aluminium</b>
Optics	<b>Zoom lens</b>
UGR	<b>n-v-t-</b>
IP class	<b>IP20 (naar boven)/IP40 (naar beneden)</b>
CRI	<b>CRI97</b>
CCT	<b>2700K, 3000K, 3500K, 4000K, Tunable White</b>
Control	<b>1-10V dimmable, Casambi dimmable, DALI dimmable, Optional</b>
Emergency lighting	<b>N/A</b>
Efficiency	<b>&gt;100lm/W</b>
Photobiological safety	<b>IEC 62471: RG1 (low risk)</b>
Insulation class	<b>Class I</b>
Power factor	<b>&gt;0.9</b>
Ambient temperature	<b>-20°C / +40°C</b>
Options	<b>220-240V, 50 / 60Hz, 93 100 100 100 100, Phase track, Integrated, L90B50@60, 000h (Tq 25°C), N/A, On request, Adjustable, Round, SDCM=2</b>
Brand	<b>Atomis</b>
Category	<b>Track luminaires</b>

## Product photos

Atmosphere and product images



## Specification text

Zumo 90 Vario is a zoomable LED spot for standard 3-phase track. The spot features a powerful LED with a high colour rendering index (CRI > 97). The beam can be continuously adjusted from a 12° spot to a 55° wide flood simply by turning the zoom lens. Zumo 90 Vario spots are particularly suitable for lighting galleries, museums and art exhibitions. - Can be used on standard high-voltage track - High CRI (> 97) colour rendering index - Continuously adjustable beam from 12° spot to 55° wide flood - Flicker-free dimming (in accordance with IEEE 1789) at the spot - Particularly suitable for lighting galleries, museums and exhibition spaces

## Information

### Note

Specifications depend on the project and configuration. Always consult the current technical documentation.

This datasheet is compiled from structured product information based on XML source data and the current source page. Specifications may vary per project configuration.

Atomis Architectural Lighting · atomislighting.com · The Netherlands

Generated on 9 July 2026