



MYOS-CG MULTIOPTIC®

Myos-CG Multioptic, a modular LED luminaire for use in suspended ceilings with concealed grid structures. This luminaire contains a set of 99 mid-power LEDs behind a decorative aperture mask. Each LED is equipped with an individual secondary lens that provides excellent light distribution with low glare (UGR<16 - UGR<19).

- Suitable for use in combination with all common suspended ceiling systems
- Architectural appearance
- Multioptic® lens system, which provides excellent light distribution with low glare (UGR<16 - UGR<19)

Downloads

[Photometry Myos-CG square](#)

Categories: [Concealed grid luminaires](#)



Myos-CG Multioptic, a modular LED luminaire for use in suspended ceilings with concealed grid structures. This luminaire contains a set of 99 mid-power LEDs behind a decorative aperture mask. Each LED is equipped with an individual secondary lens that provides excellent light distribution with low glare (UGR<16 - UGR<19).

- Suitable for use in combination with all common suspended ceiling systems
- Architectural appearance
- Multioptic® lens system, which provides excellent light distribution with low glare (UGR<16 - UGR<19)

Downloads

[Photometry Myos-CG square](#)

NOTES

ADDITIONAL INFORMATION

Kleurtemperatuur	3000K, 4000K
Driver positie	Bevestigd aan het armatuur, Losliggende driver
Producttoepassing	Gemeentehuizen, Horeca, Kantoor, Onderwijs, Retail
Energielabel	A++
Glare (UGR)	
Lengte	
Voltage / frequency	
Verwachte levensduur	L90B50@60.000h (Tq 25°C)
Primaire aansluitingen	GST18i3, GST18i5 pastelblauw, Kabel, Op de driver
Kleurweergaveindex (CRI)	CRI80
Noodverlichting	1 uur noodstroom, Optioneel, Optioneel 1 uur autonomie autotest
Productkleur	Op aanvraag, RAL9010 mat, RAL9010 mat structuur, RAL9011 mat, RAL9011 mat structuur, RAL9016 mat, RAL9016 mat structuur
Air extraction	Optioneel
CIE Flux code	76 96 99 99 100
Isolatieklasse	Klasse-II
Kleurconsistentie (SDCM)	SDCM=3
Hoogte	
IP-class	IP20 (naar boven)/IP40 (naar beneden)
Materiaal	acrylaat, Staal
Omgevingstemperatuur	-20°C / +40°C
Optiek	Lens en louver
Oriëntatie	Omlaag
Powerfactor	>0.9
Vorm	Vierkant
Bevestiging	Inbouw
Breedte	
Packaging dimensions	Bulkverpakking
C-Haak hoogte	Op aanvraag
Fotobiologische veiligheid	IEC 62471: RG1 (laag risico)

