



MYOS-M MULTIOPTIC® LINEAR

Myos-M Multioptic Linear is a series of innovative recessed luminaires with mid-power LED modules, utilizing Multioptic® lens technology, specifically designed for use with visible grid suspended ceilings. The optical system features a lens array of 99 mid-power LEDs behind a decorative diaphragm mask.

- Integrates seamlessly into visible grid ceilings
- Architectural design
- Equipped with 99 lenses (UGR < 16-19)

Downloads

[Photometry Myos-M Linear](#)

Categories: [Recessed and lay-in luminaires](#)



Myos-M Multioptic Linear is a series of innovative recessed luminaires with mid-power LED modules, utilizing Multioptic® lens technology, specifically designed for use with visible grid suspended ceilings. The optical system features a lens array of 99 mid-power LEDs behind a decorative diaphragm mask.

- Integrates seamlessly into visible grid ceilings
- Architectural design
- Equipped with 99 lenses (UGR< 16-19)

Downloads

[Photometry Myos-M Linear](#)

NOTES

ADDITIONAL INFORMATION

Kleurtemperatuur	3000K, 4000K
Driver positie	Bevestigd aan het armatuur, Losliggende driver
Breedte	295mm
Energie label	A++
Glare (UGR)	
Lengte	
Voltage / frequency	
Verwachte levensduur	L90B50@60.000h (Tq 25°C)
Primaire aansluitingen	GST18i3, GST18i5 pastelblauw, Kabel, Op de driver
Kleurweergaveindex (CRI)	CRI80
Productkleur	Op aanvraag, RAL9010 mat, RAL9010 mat structuur, RAL9011 mat, RAL9011 mat structuur, RAL9016 mat, RAL9016 mat structuur
Lichtregeling	1-10V gedimd, Casambi gedimd, DALI gedimd, Optioneel
Noodverlichting	1 uur noodstroom, Optioneel, Optioneel 1 uur autonomie autotest
Producttoepassing	Gemeentehuizen, Horeca, Kantoor, Onderwijs, Retail
Luminaire efficacy	>155lm/W
Air extraction	Optioneel
CIE Flux code	76 96 99 99 100
Isolatieklasse	Klasse-II
Kleurconsistentie (SDCM)	SDCM=3
Hoogte	
IP-class	IP20 (naar boven)/IP40 (naar beneden)
Materiaal	acrylaat, Staal
Omgevingstemperatuur	-20°C / +40°C
Optiek	Multioptic® lenstechnologie
Oriëntatie	Omlaag
Powerfactor	>0.9
Vorm	Rechthoekig
Bevestiging	Inbouw
Packaging dimensions	Bulkverpakking

Fotobiologische veiligheid

IEC 62471: RG1 (laag risico)

