



ULTRALIGHT-SAPP

Ultralight-SAPP is an elegant, slim LED fixture featuring a row of medium-power LEDs, each with its own lens and louvers. This fixture is specifically designed for use in linear louvre ceilings.

- Elegant, slim design for use in linear louvered ceilings
- Excellent low-glare task lighting according to EN-12.464/1 for office use
- Available in matte white or matte black textured coating

Downloads

[Photometrics Ultralight](#)

Create your own product, download the PDF specification sheet or add to the quotation:

Categories: [Klimaatplafond armaturen](#)



Ultralight-SAPP is an elegant, slim LED fixture featuring a row of medium-power LEDs, each with its own lens and louvers. This fixture is specifically designed for use in linear louvre ceilings.

- Elegant, slim design for use in linear louvered ceilings
- Excellent low-glare task lighting according to EN-12.464/1 for office use
- Available in matte white or matte black textured coating

Downloads

[Photometrics Ultralight](#)

Create your own product, download the PDF specification sheet or add to the quotation:

NOTES

ADDITIONAL INFORMATION

Driver positie	Losliggende driver
Producttoepassing	Gemeentehuizen, Horeca, Kantoor, Onderwijs, Retail
Vorm	Rechthoekig
Fotobiologische veiligheid	IEC 62471: RG1 (laag risico)
Kleurconsistentie (SDCM)	SDCM=3
Omgevingstemperatuur	-20°C / +40°C
Kleurtemperatuur	Tunable White, 2700K, 3000K, 3500K, 4000K
Lichtregeling	1-10V gedimd, Casambi gedimd, DALI gedimd, Optioneel
Noodverlichting	1 uur noodstroom, Optioneel, Optioneel 1 uur autonomie autotest
Primaire aansluitingen	GST18i3, GST18i5 pastelblauw, Kabel, Op de driver
Productkleur	Op aanvraag, RAL9010 mat, RAL9010 mat structuur, RAL9011 mat, RAL9011 mat structuur, RAL9016 mat, RAL9016 mat structuur
Luminaire efficacy	>133lm/W
Bevestiging	Plafondmontage
Optiek	Lens en louwer
Materiaal	Plastic, Staal
Breedte	21mm
Kleurweergaveindex (CRI)	CRI80, CRI90
Glare (UGR)	<19
CIE Flux code	100 100 100 100 100
Verwachte levensduur	L90B50@60.000h (Tq 25°C)
Voltage / frequency	220-240V, 50 / 60Hz
Powerfactor	>0.9
Isolatieklasse	Klasse-II
Oriëntatie	Omlaag
Energie label	A++

