



ZENDER

Zender, a wall-mounted LED fixture, is designed for architectural indoor lighting of vertical surfaces such as walls, corridors and stairs. Light emitted by an internally mounted LED strip directed toward the wall is first diffused by a double frosted diffuser and then reflected upward and downward, creating a softly illuminated wall.

- Robust design fixture for wall mounting suitable for corridors and entrance halls in public spaces of schools, etc.
- Available in 300 mm wide and 600 mm wide sizes
- Emergency versions available
- Can be mounted horizontally and vertically

Downloads

[Photometrics Zender](#) [BIM files Zender](#)

Categories: [Surface-mounted luminaires](#)



Zender, a wall-mounted LED fixture, is designed for architectural indoor lighting of vertical surfaces such as walls, corridors and stairs. Light emitted by an internally mounted LED strip directed toward the wall is first diffused by a double frosted diffuser and then reflected upward and downward, creating a softly illuminated wall.

- Robust design fixture for wall mounting suitable for corridors and entrance halls in public spaces of schools, etc.
- Available in 300 mm wide and 600 mm wide sizes
- Emergency versions available
- Can be mounted horizontally and vertically

Downloads

[Photometrics Zender](#) [BIM files Zender](#)

NOTES

ADDITIONAL INFORMATION

Isolatieklasse	Klasse-I
Producttoepassing	Expositieruimtes, Gemeentehuizen, Horeca, Kantoor, Onderwijs, Retail
Energielabel	A+
Kleurtemperatuur	2700K, 3000K, 4000K
Voltage / frequency	
Verwachte levensduur	L90B50@60.000h (Tq 25°C)
IK class	
Kleurweergaveindex (CRI)	CRI80, CRI90
IP-class	IP20 (naar boven)/IP40 (naar beneden)
Lichtregeling	1-10V gedimd, Casambi gedimd, DALI gedimd, Optioneel
Noodverlichting	1 uur noodstroom, Optioneel, Optioneel 1 uur autonomie autotest
Productkleur	Op aanvraag, RAL9010 mat, RAL9010 mat structuur, RAL9011 mat, RAL9011 mat structuur, RAL9016 mat, RAL9016 mat structuur
Packaging dimensions	Bulkverpakking
Air extraction	n.v.t.
CIE Flux code	n.v.t.
Kleurconsistentie (SDCM)	SDCM=3
Materiaal	acrylaat, Staal
Omgevingstemperatuur	-20°C / +40°C
Powerfactor	>0.9
Vorm	Rechthoekig
Bevestiging	Wandmontage
Optiek	Opalen diffusor
Driver positie	Geïntegreerd
Glare (UGR)	Niet van toepassing
Fotobiologische veiligheid	IEC 62471: RG1 (laag risico)

PHOTOMETRIC DATA

Zender 300 10W 950lm 3000K CRI80

Zender 300 10W 1000lm 4000K CRI80

Zender 600 19W 1900lm 3000K CRI80

Zender 600 19W 2050lm 4000K CRI80