



ZUMO 100 VARIO WHITE

Zumo 100 Vario is a zoomable LED spotlight for standard track rails. The spotlight features a powerful LED with a high color rendering index (CRI > 97). The light beam can be continuously adjusted from 12° spot to 55° wide flood by simply rotating the zoom lens. Zumo 100 Vario spotlights are particularly suitable for lighting galleries, museums and art exhibitions.

- Can be used on standard high-voltage tracks
- High CRI (> 97) color rendering index
- Continuously adjustable light beam from 12° spot to 55° wide flood
- Stroboscopic-free dimming (according to IEEE 1789) on the spot
- Particularly suitable for lighting galleries, museums and exhibition spaces

Downloads

[Photometrics Zumo 100 Vario](#)

Categories: [Track luminaires](#)



Zumo 100 Vario is a zoomable LED spotlight for standard track rails. The spotlight features a powerful LED with a high color rendering index (CRI > 97). The light beam can be continuously adjusted from 12° spot to 55° wide flood by simply rotating the zoom lens. Zumo 100 Vario spotlights are particularly suitable for lighting galleries, museums and art exhibitions.

- Can be used on standard high-voltage tracks
- High CRI (> 97) color rendering index
- Continuously adjustable light beam from 12° spot to 55° wide flood
- Stroboscopic-free dimming (according to IEEE 1789) on the spot
- Particularly suitable for lighting galleries, museums and exhibition spaces

Downloads

[Photometrics Zumo 100 Vario](#)

NOTES

ADDITIONAL INFORMATION

Isolatieklasse	Klasse-I
Producttoepassing	Expositieruimtes, Gemeentehuizen, Horeca, Kantoor, Onderwijs, Residentieel, Retail
Energielabel	A+
Kleurtemperatuur	Tunable White, 2700K, 3000K, 3500K, 4000K
Kleurconsistentie (SDCM)	SDCM=2
Voltage / frequency	
Materiaal	acrylaat, Aluminum
Packaging dimensions	Bulkverpakking
Bevestiging	Rail
Kleurweergaveindex (CRI)	CRI80, CRI90, CRI97
IP-class	
Lichtregeling	1-10V gedimd, Casambi gedimd, DALI gedimd, Optioneel
Primaire aansluitingen	Fase track, Rails
Productkleur	Mat wit, Mat zwart, Op aanvraag
Air extraction	n.v.t.
Driver positie	Geïntegreerd
Verwachte levensduur	L90B50@50.000h (Tq 25°C)
Omgevingstemperatuur	-20°C / +40°C
Optiek	Zoomlens
Oriëntatie	Richtbaar
Powerfactor	>0.9
Vorm	Rond
Spot bundle (FWHM)	12° – 55°
Lengte	
Breedte	
Fotobiologische veiligheid	IEC 62471: RG1 (laag risico)
ANSI/IES TM-30-18	Erkend

