



MOONGLOW ROUND 290

Moonglow round 290 is a surface-mounted fixture with a decorative luminous disc-shaped acrylic diffuser.

- Effective lighting with decorative architectural appeal
- Wall or ceiling mount
- Matte black or matte white finish
- IK6 impact resistant for use in corridors and stairwells
- Emergency lighting version available




Downloads

[Photometrics Moonglow round 290 BIM files](#) [Photometrics Moonglow round 290](#)

Categories: [Surface-mounted luminaires](#)



PRODUCT IMAGES





Moonglow round 290 is a surface-mounted fixture with a decorative luminous disc-shaped acrylic diffuser.

- Effective lighting with decorative architectural appeal
- Wall or ceiling mount
- Matte black or matte white finish
- IK6 impact resistant for use in corridors and stairwells
- Emergency lighting version available

Downloads

[Photometrics Moonglow round 290 BIM files](#) [Photometrics Moonglow round 290](#)

NOTES

ADDITIONAL INFORMATION

Application	Education, Hospitality, Office, Public spaces
Shape	Round
CIE Flux code	
Color temperature	Tunable White, 2700K
Kleurconsistentie (SDCM)	SDCM=2
Voltage / frequency	
Expected lifespan	L90B50@60,000h (Tq 25°C)
IK class	
Color Rendering Index (CRI)	CRI80, CRI90
Material	Acrylic, Aluminum
Product Color	On request, RAL9010 mat, RAL9010 mat structuur, RAL9011 mat, RAL9011 mat structuur, RAL9016 mat, RAL9016 mat structuur
IP Rating	IP20 (upwards)/IP40 (downwards)
Lighting control	1-10V dimming, Casambi dimming, DALI dimming, Optional
Emergency lighting	1 hour emergency power, Optional, Optional 1 hour autonomy self-test
Self-adhesive dust cover	No
Spot bundle (FWHM)	
Primary connections	On the driver
Packaging dimensions	Bulk packaging
Luminaire efficacy	>80lm/W
Air extraction	N/A
Product family	Moonglow
Ambient temperature	-20°C / +40°C
Optics	Opalen diffusor
Product Glare (UGR)	Not applicable
Power factor	>0.9
Insulation Class	Class-I
Product Confirmation	Ceiling mounting, Wall mounting
Width	50mm
Driver position	Integrated

Energy Rating A

Photobiological safety IEC 62471: RG1 (low risk)

PHOTOMETRIC DATA

Moonglow Round 290 11W 1000lm 3000K CRI80 G8
Moonglow Round 290 11W 1050lm 4000K CRI80 G8
Moonglow Round 290 15W 1300lm 3000K CRI80 G8
Moonglow Round 290 15W 1400lm 4000K CRI80 G8
Moonglow Round 290 20W 1650lm 3000K CRI80 G8
Moonglow Round 290 20W 1700lm 4000K CRI80 G8
Moonglow Round 290 HO 24W 1950lm 3000K CRI80 G8
Moonglow Round 290 HO 24W 2000lm 4000K CRI80 G8
Moonglow Round 290 HO 33W 2500lm 3000K CRI80 G8
Moonglow Round 290 HO 33W 2600lm 4000K CRI80 G8

Downloads

[Photometrics Moonglow round 290 BIM files](#) [Photometrics Moonglow round 290](#)

DOWNLOADS

Downloads

[Photometrics Moonglow round 290 BIM files](#) [Photometrics Moonglow round 290](#)