

## **SIRIO EASY-KLIMAPLUS®**

Sirio Easy-KlimaPlus, a 21.5 mm slim linear lighting fixture with lenses for use in Interalu Sirio Easy-KlimaPlus® ceilings.

- Fully integrated into [Interalu](#) Easy Klima Plus® ceilings
- Easy installation with magnetic mounting
- Available in three lengths 900, 1200 and 1500
- Unique lens configuration UGR< 19 office-compatible




### **Downloads**

[Photometrics Sirio EKP](#)



**Categories:** [Climate ceiling fixtures](#)



## PRODUCT IMAGES



f-waardering volgens UGR																	
		Perspectief dwars t.o.v. lampenpas						Perspectief lengs t.o.v. lampenpas									
Ruimteafmeting	X	Y	2H	4H	6H	8H	12H	2H	4H	6H	8H						
μ Plafond	70	70	50	50	30	30	70	70	50	50	30						
μ Muren	50	30	50	30	30	30	50	30	50	30	30						
μ Vloer	20	20	20	20	20	20	20	20	20	20	20						
Variatie op evenwichtspositie voor lampafstanden S																	
S = 1.0H			+3.3	/ -13.9				+4.2	/ -13.3								
S = 1.5H			+6.0	/ -13.9				+7.0	/ -14.6								
S = 2.0H			+8.0	/ -14.2				+8.0	/ -15.2								
Standaardtafel																	
BKO0						BK00											
Correctie-opteltall																	
0.3																	
Gecorrigeerde verbindingsindicatie in relatie tot 7726lm Totale lichtstroom																	





Sirio Easy-KlimaPlus, a 21.5 mm slim linear lighting fixture with lenses for use in Interalu Sirio Easy-KlimaPlus® ceilings.

- Fully integrated into [Interalu](#) Easy Klima Plus® ceilings
- Easy installation with magnetic mounting
- Available in three lengths 900, 1200 and 1500
- Unique lens configuration UGR< 19 office-compatible

## Downloads

[Photometrics Sirio EKP](#)

## **NOTES**

---

---

---

---

---

## ADDITIONAL INFORMATION

<b>Insulation Class</b>	Class II
<b>Driver position</b>	Loose driver
<b>Application</b>	Education, Hospitality, Office, Public spaces
<b>Energy Rating</b>	
<b>Product Glare (UGR)</b>	
<b>Color temperature</b>	Tunable White, 2700K
<b>Lengte</b>	
<b>Voltage / frequency</b>	
<b>Expected lifespan</b>	L90B50@60,000h (Tq 25°C)
<b>Color Rendering Index (CRI)</b>	CRI80, CRI90
<b>Product Color</b>	Matte black, Matte white, On request
<b>Lighting control</b>	1-10V dimming, Casambi dimming, DALI dimming, Optional
<b>Emergency lighting</b>	1 hour emergency power, Optional, Optional 1 hour autonomy self-test
<b>Primary connections</b>	GST18i3, GST18i5 pastelblauw, Kabel, On the driver
<b>Optics</b>	Lens en louver
<b>Self-adhesive dust cover</b>	No
<b>Spot bundle (FWHM)</b>	
<b>Luminaire efficacy</b>	>130lm/W
<b>Air extraction</b>	N/A
<b>CIE Flux code</b>	93 100 100 100 100
<b>Kleurconsistentie (SDCM)</b>	SDCM=3
<b>Hight</b>	
<b>IP Rating</b>	IP20 (upwards)/IP40 (downwards)
<b>Material</b>	Acrylic, Steel
<b>Ambient temperature</b>	-20°C / +40°C
<b>Oriëntatie</b>	Down
<b>Packaging dimensions</b>	Bulk packaging
<b>Power factor</b>	>0.9
<b>Shape</b>	Rectangular
<b>Product Confirmation</b>	Recessed

**Width**

**Photobiological safety** IEC 62471: RG1 (low risk)

**Specifications** G7D1 / 06-02-2025

