



## ULTRALIGHT-SAPP

Ultralight-SAPP is an elegant, slim LED fixture featuring a row of medium-power LEDs, each with its own lens and louvers. This fixture is specifically designed for use in linear louvre ceilings.

- Elegant, slim design for use in linear louvered ceilings
- Excellent low-glare task lighting according to EN-12.464/1 for office use
- Available in matte white or matte black textured coating

### Downloads

[Photometrics Ultralight](#)

**Create your own product, download the PDF specification sheet or add to the quotation:**

**Categories:** [Baffle luminaires](#)



Ultralight-SAPP is an elegant, slim LED fixture featuring a row of medium-power LEDs, each with its own lens and louvers. This fixture is specifically designed for use in linear louvre ceilings.

- Elegant, slim design for use in linear louvered ceilings
- Excellent low-glare task lighting according to EN-12.464/1 for office use
- Available in matte white or matte black textured coating

## **Downloads**

[Photometrics Ultralight](#)

**Create your own product, download the PDF specification sheet or add to the quotation:**

## NOTES

---

---

---

---

---

---

## ADDITIONAL INFORMATION

<b>Driver position</b>	Loose driver
<b>Application</b>	Education, Hospitality, Office, Public spaces
<b>Shape</b>	Rectangular
<b>Photobiological safety</b>	IEC 62471: RG1 (low risk)
<b>Kleurconsistentie (SDCM)</b>	SDCM=3
<b>Ambient temperature</b>	-20°C / +40°C
<b>Color temperature</b>	Tunable White, 2700K
<b>Lighting control</b>	1-10V dimming, Casambi dimming, DALI dimming, Optional
<b>Emergency lighting</b>	1 hour emergency power, Optional, Optional 1 hour autonomy self-test
<b>Primary connections</b>	GST18i3, GST18i5 pastelblauw, Kabel, On the driver
<b>Product Color</b>	On request, RAL9010 mat, RAL9010 mat structuur, RAL9011 mat, RAL9011 mat structuur, RAL9016 mat, RAL9016 mat structuur
<b>Spot bundle (FWHM)</b>	Not applicable
<b>Luminaire efficacy</b>	>133lm/W
<b>Product family</b>	Ultralight
<b>Product Confirmation</b>	Ceiling mounting
<b>Optics</b>	Lens en louver
<b>Material</b>	Plastic, Steel
<b>Width</b>	
<b>Color Rendering Index (CRI)</b>	CRI80, CRI90
<b>Product Glare (UGR)</b>	
<b>CIE Flux code</b>	
<b>Expected lifespan</b>	L90B50@60,000h (Tq 25°C)
<b>Voltage / frequency</b>	220-240V, 50 / 60Hz
<b>Power factor</b>	>0.9
<b>Insulation Class</b>	Class II
<b>Oriëntatie</b>	Down
<b>Energy Rating</b>	

