



ZUMO 60 VARIO WHITE

Zumo 60 Vario is a zoomable LED spotlight for standard 3-phase track systems. The spotlight features a powerful LED with a high color rendering index (CRI> 97). The light beam can be continuously adjusted from 10° spot to 50° wide flood by simply rotating the zoom lens. Zumo 60 Vario spotlights are particularly suitable for lighting galleries, museums and art exhibitions.

- Compact design LED spotlight (ø60mm) for standard track systems
- High CRI (> 97) color rendering index
- Continuously adjustable light beam from 10° spot to 50° wide flood
- Stroboscopic-free dimming (according to IEEE 1789) on the spot
- Particularly suitable for lighting galleries, museums and exhibition spaces

Downloads






[Photometrics Nano 35](#)

Create your own product, download the PDF specification sheet or add to the quotation:

Categories: [Track luminaires](#)



PRODUCT IMAGES





Zumo 60 Vario is a zoomable LED spotlight for standard 3-phase track systems. The spotlight features a powerful LED with a high color rendering index (CRI > 97). The light beam can be continuously adjusted from 10° spot to 50° wide flood by simply rotating the zoom lens. Zumo 60 Vario spotlights are particularly suitable for lighting galleries, museums and art exhibitions.

- Compact design LED spotlight (ø60mm) for standard track systems
- High CRI (> 97) color rendering index
- Continuously adjustable light beam from 10° spot to 50° wide flood
- Stroboscopic-free dimming (according to IEEE 1789) on the spot
- Particularly suitable for lighting galleries, museums and exhibition spaces

Downloads

[Photometrics Nano 35](#)

Create your own product, download the PDF specification sheet or add to the quotation:

NOTES

ADDITIONAL INFORMATION

Insulation Class	Class-I
Application	Education, Hospitality, Office, Public spaces
Energy Rating	
Color temperature	2700K
Kleurconsistentie (SDCM)	SDCM=2
Material	Aluminum, Plastic
Packaging dimensions	Bulk packaging
Product Confirmation	Rail
Product Glare (UGR)	Not applicable
Color Rendering Index (CRI)	CRI80, CRI90, CRI97
Lighting control	1-10V dimming, Casambi dimming, DALI dimming, Optional
Emergency lighting	1 hour emergency power, Optional, Optional 1 hour autonomy self-test
Primary connections	Fase track, Rails
Product Color	Matte black, Matte white, On request
Self-adhesive dust cover	No
Luminaire efficacy	>85lm/W
Air extraction	N/A
Product family	Zumo
Driver position	Integrated
Expected lifespan	L90B50@50.000h (Tq 25°C)
Ambient temperature	-20°C / +40°C
Optics	Zoom lens
Oriëntatie	Adjustable
Power factor	>0.9
Shape	Round
Spot bundle (FWHM)	10° - 50°
Photobiological safety	IEC 62471: RG1 (low risc)
ANSI/IES TM-30-18	Erkend

