



## CYLUS 40 WHITE

The **Cylus 40 White** is a high-quality architectural LED fixture specifically designed for **modern offices, town halls, public spaces, counters, and reception areas**. Thanks to its elegant **tubular design of just 40 mm**, made from durable **aluminum**, this fixture offers a perfect balance between design, performance, and functionality.

- Slim **40 mm aluminum light tube**
- Comfortable **reflector optics** for task and accent lighting
- **Integrated driver** for a sleek and interference-free design
- Optimal application in **offices, public buildings, counters, entrances, and waiting areas**
- Modern look in a durable **matte white finish**
- **Surface-mounted or recessed module optional.**
- Designed for long-term reliability and professional projects

Categories: [Pendant luminaires](#)



The **Cylus 40 White** is a high-quality architectural LED fixture specifically designed for **modern offices, town halls, public spaces, counters, and reception areas**. Thanks to its elegant **tubular design of just 40 mm**, made from durable **aluminum**, this fixture offers a perfect balance between design, performance, and functionality.

- Slim **40 mm aluminum light tube**
- Comfortable **reflector optics** for task and accent lighting
- **Integrated driver** for a sleek and interference-free design
- Optimal application in **offices, public buildings, counters, entrances, and waiting areas**
- Modern look in a durable **matte white finish**
- **Surface-mounted or recessed module optional.**
- Designed for long-term reliability and professional projects

**NOTES**

---

---

---

---

---

---

---

**ADDITIONAL INFORMATION**

<b>Air extraction</b>	N/A
<b>Energielabel</b>	A++
<b>Family</b>	cycle
<b>IP-class</b>	IP20 top / IP40 bottom
<b>Isolatieklasse</b>	Class II
<b>Kleurconsistentie (SDCM)</b>	SDCM 3
<b>Kleurtemperatuur</b>	2700K, 3000K, 3500K, 4000K
<b>Color Rendering Index (CRI)</b>	CRI97, CRI80, CRI 91
<b>Light control</b>	1-10V dimming, Casambi dimming, DALI dimming, Optional
<b>Optics</b>	Reflector
<b>Oriëntatie</b>	Down
<b>Packaging dimensions</b>	Bulk packaging
<b>Powerfactor</b>	>9
<b>Primaire aansluitingen</b>	On request, Kabel
<b>Producttoepassing</b>	Education, Hospitality, Office, Public spaces
<b>Self-adhesive dust cover</b>	N/A
<b>Verpakkingsafmetingen</b>	Bulkverpakking
<b>Voltage / frequentie</b>	220-240V, 50 / 60Hz
<b>Zelfklevende stofkap</b>	Optioneel
<b>Shape</b>	Round

