



CYLUS 50 BLACK

The Cylus 50 black is a high-quality architectural LED luminaire specifically designed for **modern offices, town halls, public spaces, counters, and reception areas**. Thanks to its elegant **tubular design of just 40 mm**, made of durable **aluminum**, this luminaire offers a perfect balance of design, performance, and functionality.

- Sleek **50 mm aluminum light tube**
- Comfortable **reflector optics** for task and accent lighting
- **Integrated driver** for a sleek and interference-free design
- Optimal application in **offices, public buildings, counters, entrances, and waiting areas**
- Modern look in a durable **matte black finish**
- **Surface-mounted or recessed module optional.**
- Designed for long-term reliability and professional projects

Categories: [Pendant luminaires](#)



The Cylus 50 black is a high-quality architectural LED luminaire specifically designed for **modern offices, town halls, public spaces, counters, and reception areas**. Thanks to its elegant **tubular design of just 40 mm**, made of durable **aluminum**, this luminaire offers a perfect balance of design, performance, and functionality.

- Sleek **50 mm aluminum light tube**
- Comfortable **reflector optics** for task and accent lighting
- **Integrated driver** for a sleek and interference-free design
- Optimal application in **offices, public buildings, counters, entrances, and waiting areas**
- Modern look in a durable **matte black finish**
- **Surface-mounted or recessed module optional.**
- Designed for long-term reliability and professional projects

NOTES

ADDITIONAL INFORMATION

Air extraction	N/A
Armaturefficiëntie	100lm/W
Bevestiging	pendant
CIE Flux code	93 100 100 100 100
Driver positie	Integrated
Energielabel	A++
Family	cycle
Photobiological safety	IEC 62471: RG1 (low risc)
Glare (UGR)	<19
IP-class	IP20 (upwards)/IP40 (downwards)
Isolatieklasse	Class II
Kleurconsistentie (SDCM)	SDCM=2
Kleurtemperatuur	2700K, 3000K, 3500K, 4000K
Color Rendering Index (CRI)	CRI97, CRI90, CRI80
Light control	1-10V dimming, Casambi dimming, DALI dimming, Optional
Luchtafzuiging	n.v.t.
Material	Acrylic, Aluminium, Steel
Emergency lighting	1 hour emergency power, Optional, Optional 1 hour autonomy self-test
Ambient temperature	-20°C / +40°C
Optics	Reflector
Oriëntatie	Down
Packaging dimensions	Bulk packaging
Powerfactor	>9
Primaire aansluitingen	On request, Kabel
Productkleur	On request
Producttoepassing	Education, Hospitality, Office, Public spaces
Self-adhesive dust cover	N/A
Verpakkingsafmetingen	Bulkverpakking
Verwachte levensduur	L90B50@60,000h (Tq 25°C)
Voltage / frequentie	220-240V, 50 / 60Hz

Shape

Round

Zelfklevende stofkap

Optioneel

LDT / PHOTOMETRICS DOWNLOADS

LDT / Photometrics downloads

All downloads can be found centrally per family at

<https://atomis.nl/ldt-photometrics/>